

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 02/10/2017 Supersedes: 06/03/2017 Version: 1.2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Trade name : JOHNSEN'S WINDSHIELD WASHER CONCENTRATION 16 FL.OZ.

Product code : 2944

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Windshield Washer Concentrate

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company P.O. BOX 139 Cleburne, Texas 76033 T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### **GHS-US** classification

Flam. Liq. 2 H225
Acute Tox. 3 (Oral) H301
Acute Tox. 3 (Dermal) H311
Acute Tox. 3 (Inhalation:dust,mist) H331
STOT SE 1 H370
Full text of H statements : see section 16

#### 2.2. Label elements

#### **GHS-US** labeling

Hazard pictograms (GHS-US)





GHS02 GHS06

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor

H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled

H370 - Causes damage to organs

Precautionary statements (GHS-US) : P210 - Keep away from heat,sparks,open flames,hot surfaces. - No smoking

P233 - Keep container tightly closed

P240 - Ground/Bond container and receiving equipment

P241 - Use explosion-proof electrical, ventilating, lighting equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P260 - Do not breathe dust,fumes,gas,mist,vapor spray P261 - Avoid breathing dust,fume,gas,mist,vapor spray P264 - Wash affected areas thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,

P302+P352 - If on skin: Wash with plenty of soap and water

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P307+P311 - If exposed: Call a poison center/doctor

P311 - Call a poison center, doctor

P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.

P321 - Specific treatment: See section 4.1 on SDS P322 - Specific treatment (see ... on this label)

P330 - Rinse mouth

P361 - Take off immediately all contaminated clothing P363 - Wash contaminated clothing before reuse

10/02/2017 EN (English US) 1/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P370+P378 - In case of fire: See Section 5.1 Extinguishing Media

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with

local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification

: None under normal conditions.

#### **Unknown acute toxicity (GHS US)**

No data available

#### **SECTION 3: Composition/Information on ingredients**

#### **Substance**

Not applicable

#### **Mixture** 3.2.

Name	Product identifier	%	GHS-US classification
Methanol	(CAS No) 67-56-1	>= 95	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
Polyethylene Glycol 200-600	(CAS No) 25322-68-3	<= 0.0045	Not classified
Nonyl Nonoxynol-5	(CAS No) 9014-93-1	<= 0.003	Not classified
Hydrogen [4-[4-(Diethylamino)-2',4'- Disulphonatobenzhydrylidene] Cyclohexa-2,5-Dien-1-ylidene] Diethylammonium, Sodium Salt	(CAS No) 129-17-9	~ 0.000001	Not classified

The exact percentage is a trade secret.

#### **SECTION 4: First aid measures**

#### **Description of first aid measures**

: IF exposed or concerned: Get medical advice/attention. Never give anything by mouth to an First-aid measures general unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Call a POISON CENTER or doctor/physician.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately First-aid measures after inhalation

call a poison center or doctor/physician.

First-aid measures after skin contact Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Wash with plenty of soap and water.

Wash contaminated clothing before reuse.

First-aid measures after eye contact Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Immediately call a poison center or doctor/physician. Obtain medical

attention if pain, blinking or redness persist.

First-aid measures after ingestion Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a poison center or doctor/physician.

## Most important symptoms and effects, both acute and delayed

: May damage fertility or the unborn child. Causes damage to organs. Symptoms/injuries

Symptoms/injuries after inhalation : Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/injuries after skin contact Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin.

Symptoms/injuries after eye contact Causes serious eye damage. Irritation of the eye tissue. Inflammation/damage of the eye

tissue. Redness of the eye tissue.

Symptoms/injuries after ingestion Fatal if swallowed. Toxic if swallowed. Swallowing a small quantity of this material will result in

serious health hazard.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## **SECTION 5: Firefighting measures**

#### **Extinguishing media**

: Foam. Dry powder. Carbon dioxide. Water spray. Sand. Suitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

#### Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.

: May form flammable/explosive vapor-air mixture. **Explosion hazard** 

10/02/2017 EN (English US) 2/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Advice for firefighters

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any Firefighting instructions

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

#### **SECTION 6: Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

General measures Remove ignition sources. Use special care to avoid static electric charges. No open flames. No

smoking.

6.1.1. For non-emergency personnel

: Gloves. Safety glasses. Protective equipment

**Emergency procedures** : Evacuate unnecessary personnel.

For emergency responders 6.1.2.

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.

**Emergency procedures** : Ventilate area.

#### 6.2. **Environmental precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### Methods and material for containment and cleaning up

: Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the For containment

leak, cut off the supply.

Methods for cleaning up Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

#### Reference to other sections

See Heading 8. Exposure controls and personal protection.

## **SECTION 7: Handling and storage**

#### Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Obtain special instructions. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust,fume,gas,mist,vapor spray. Do not

breathe dust,fumes,gas,mist,vapor spray.

Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after Hygiene measures

handling. Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating,

drinking or smoking and when leaving work.

## Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting

equipment.

Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof Storage conditions

place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

: Sources of ignition. Direct sunlight. Heat sources. Incompatible materials

## Specific end use(s)

Follow Label Directions.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. **Control parameters**

Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (mg/m³)	262 mg/m³
USA ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (mg/m³)	328 mg/m³
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³

10/02/2017 EN (English US) 3/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)				
USA OSHA OSHA PEL (TWA) (ppm) 200 ppm				
9.2 Evacure controls				

8.2. Exposure controls

Appropriate engineering controls : Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

Personal protective equipment : Safety glasses. Gloves. Avoid all unnecessary exposure.



Materials for protective clothing : GIVE EXCELLENT RESISTANCE:

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

Environmental exposure controls : Avoid release to the environment.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical state : Liquid Color : Blue.

Odor : Mild . Odourless.
Odor threshold : 4.2 - 5960 ppm

pH :  $\approx 7$ Relative evaporation rate (butyl acetate=1) : 4.1

Melting point : No data available

Freezing point : -97.8

Boiling point : 64.7 °C

Flash point : 11 °C

Critical temperature : 239.4 °C

Auto-ignition temperature : 464 °C

Decomposition temperature : Not Deter

Decomposition temperature : Not Determined
Flammability (solid, gas) : No data available
Vapor pressure : 12.8 kPa @ 20 deg C

Critical pressure : 77.77 bar

Relative vapor density at 20  $^{\circ}\text{C}$   $\phantom{\text{C}}$  : No data available

Relative density : 0.792

Solubility : Soluble in alcohols. Soluble in water.

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available

Explosion limits : 36.5 vol % Upper Explosive Limit (UEL)

9.2. Other information

VOC content : > 98 %

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10/02/2017 EN (English US) 4/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Possibility of hazardous reactions

Not established.

#### 10.4. **Conditions to avoid**

Direct sunlight. Extremely high or low temperatures. Open flame.

#### Incompatible materials

Strong acids. Strong bases.

#### **Hazardous decomposition products**

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

## **SECTION 11: Toxicological information**

#### Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:dust,mist: Toxic if

inhaled.

Polyethylene Glycol 200-600 (25322-68-3)			
LD50 oral rat	> 15000 mg/kg (Rat)		
LD50 dermal rabbit	> 20000 mg/kg (Rabbit)		
Hydrogen [4-[4-(Diethylamino)-2',4'-Disulphonatobenzhydrylidene] Cyclohexa-2,5-Dien-1-ylidene] Diethylammonium, Sodium Salt (129-17-9)			
LD50 oral rat	3001 mg/kg (Rat)		
Methanol (67-56-1)			
I DEC and not	OFOO as all a body consists and lighting as FOO/ assumed as better		

Methanol (67-56-1)	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air

: Not classified Skin corrosion/irritation pH: ≈ 7

Serious eye damage/irritation : Not classified pH: ≈ 7

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified Based on available data, the classification criteria are not met

Carcinogenicity Not classified

3 IARC group

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Causes damage to organs.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Fatal if swallowed. Based on available data, the classification criteria are not met. Toxic if

swallowed. Toxic in contact with skin. Toxic if inhaled.

Symptoms/injuries after inhalation

Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/injuries after skin contact

Repeated exposure to this material can result in absorption through skin causing significant

health hazard. Toxic in contact with skin.

Symptoms/injuries after eye contact

Causes serious eye damage. Irritation of the eye tissue. Inflammation/damage of the eye

tissue. Redness of the eye tissue.

: Fatal if swallowed. Toxic if swallowed. Swallowing a small quantity of this material will result in Symptoms/injuries after ingestion

serious health hazard

#### **SECTION 12: Ecological information**

#### 12.1. **Toxicity**

Polyethylene Glycol 200-600 (25322-68-3)	
LC50 fish 2	> 5000 mg/l (LC50; 24 h)
Threshold limit algae 2	500 mg/l (EC0; 720 h)
Methanol (67-56-1)	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)

10/02/2017 EN (English US) 5/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methanol (67-56-1)	
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water;
·	Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)
12.2. Persistence and degradability	
JOHNSEN'S WINDSHIELD WASHER CO	NCENTRATION 16 FL.OZ.
Persistence and degradability	Not established.
Polyethylene Glycol 200-600 (25322-68-3	3)
Persistence and degradability	Biodegradability in water: no data available. Not established.
Nonyl Nonoxynol-5 (9014-93-1)	·
Persistence and degradability	Not established.
Hydrogen [4-[4-(Diethylamino)-2',4'-Disu 17-9)	ılphonatobenzhydrylidene] Cyclohexa-2,5-Dien-1-ylidene] Diethylammonium, Sodium Salt (129-
Persistence and degradability	Biodegradability in water: no data available.
Methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.8 (Literature study)
2.3. Bioaccumulative potential	
JOHNSEN'S WINDSHIELD WASHER CO	NCENTRATION 16 FL.OZ.
Bioaccumulative potential	Not established.
Polyethylene Glycol 200-600 (25322-68-3	3)
Log Pow	-1.2
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.
Nonyl Nonoxynol-5 (9014-93-1)	
Bioaccumulative potential	Not established.
Hydrogen [4-[4-(Diethylamino)-2',4'-Disu	ulphonatobenzhydrylidene] Cyclohexa-2,5-Dien-1-ylidene] Diethylammonium, Sodium Salt (129
Log Pow	-5.340 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.
Methanol (67-56-1)	·
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
12.4. Mobility in soil	
Methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value
12.5. Other adverse effects	
Other information	: Avoid release to the environment.
SECTION 13: Disposal considera	tions
13.1. Waste treatment methods	Dispose in a safe manner in accordance with legal/national regulations. Dispose of
Waste disposal recommendations	<ul> <li>Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.</li> </ul>
Additional information	: Handle empty containers with care because residual vapors are flammable.
Teelegy wests meterials	Avoid to the oppose to the opp

## Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

10/02/2017 EN (English US) 6/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1230, Methanol (11C c.c.), 3, II, Limited Quantity
ICAO/IATA (air): UN1230, Methanol (11C c.c.), 3 (6.1), II, Limited Quantity
IMO/IMDG (water): UN1230, Methanol (11C c.c.), 3 (6.1), II, Limited Quantity

Special Provisions: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional

Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55

C (1.3 bar at 131 F) are authorized

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities

(in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Methanol (11C c.c.)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



DOT Symbols : +- Fixes (cannot be altered) proper shipping name, hazard class, and packing group,I - Proper

shipping name appropriate for international and domestic transportation

Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

### 14.3. Additional information

Other information : No supplementary information available.

#### **Overland transport**

No additional information available

#### Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Subsidiary risks (IMDG) : 6.1

## Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

Subsidiary risk (IATA) : 6.1

10/02/2017 EN (English US) 7/9

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information				
15.1. US Federal regulations				
JOHNSEN'S WINDSHIELD WASHER CONCEN	ITRATION 16 FL.OZ.			
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard			
Methanol (67-56-1)				
Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Listed on the United States SARA Section 355				
SARA Section 311/312 Hazard Classes  Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard				

#### 15.2. International regulations

#### CANADA

CANADA			
JOHNSEN'S WINDSHIELD WASHER CONCENTRATION 16 FL.OZ.			
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects		
Methanol (67-56-1)			
Listed on the Canadian DSL (Domestic Substances List)			
WHMIS Classification  Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxi Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects			

## **EU-Regulations**

## Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

## Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

**Developmental Toxicity** 

T; R23/24/25

T; R39/23/24/25

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

## Methanol (67-56-1)

Carcinogens List

Listed on the Canadian IDL (Ingredient Disclosure List)

## 15.3. US State regulations

	The state of the s					
JOHNSEN'S WINDSHIELD WASHER CONCENTRATION 16 FL.OZ.						
U.S California - Proposition 65 - Carcinogens List No						
U.S California - Proposition Toxicity	n 65 - Developmental	Yes				
U.S California - Proposition 65 - Reproductive No Toxicity - Female						
U.S California - Proposition Toxicity - Male	n 65 - Reproductive	S5 - Reproductive No				
State or local regulations		U.S California - Proposition 65				
Polyethylene Glycol 200-60	00 (25322-68-3)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)		
No	No	No	No			
Nonyl Nonoxynol-5 (9014-93-1)						
U.S California - Proposition 65 -	U.S California - Proposition 65 -	U.S California - Proposition 65 -	U.S California - Proposition 65 -	Non-significant risk level (NSRL)		

10/02/2017 EN (English US)

Reproductive Toxicity -

Reproductive Toxicity -

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nonyl Nonoxynol-5 (9014-93-1)				
		Female	Male	
No	No	No	No	
Hydrogen [4-[4-(Diethylam	ino)-2',4'-Disulphonatobenzh	nydrylidene] Cyclohexa-2,5-Die	en-1-ylidene] Diethylammonium	, Sodium Salt <b>(129-17-9)</b>
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	, ,
	,	Female	Male	
No	No	No	No	
Methanol (67-56-1)				
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	, ,
Ŭ	,	Female	Male	
No	Yes	No	No	
Mathemat (C7 FC 4)	Methodal (C7 EC 4)			

#### Methanol (67-56-1)

#### State or local regulations

U.S. - California - Proposition 65 New Jersey Right-to-Know Florida Right to Know

U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List

## **SECTION 16: Other information**

Indication of changes : Revision - See : \*.

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H370	Causes damage to organs

NFPA health hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



## **HMIS III Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

10/02/2017 EN (English US) 9/9