



# JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 09/25/2017

Supersedes:02/06/2017

Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.  
Product code : 4695-6

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel Injector Cleaner

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 4 H227  
Carc. 2 H351  
Asp. Tox. 1 H304

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger  
Hazard statements (GHS-US) : H227 - Combustible liquid  
H304 - May be fatal if swallowed and enters airways  
H351 - Suspected of causing cancer  
Precautionary statements (GHS-US) : P201 - Obtain special instructions  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P331 - Do NOT induce vomiting  
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

# JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Name  | Product identifier  | %             | GHS-US classification  |
|---|---------------------|---------------|--|
| Distillates (Petroleum), Hydrotreated Light | (CAS No) 64742-47-8 | >= 95         | Asp. Tox. 1, H304  |
| Naphtha, Hydrotreated Heavy                 | (CAS No) 64742-48-9 | 0.104 - 0.972 | Asp. Tox. 1, H304  |
| Paraffins (Petroleum), Normal C5-20         | (CAS No) 64771-72-8 | < 1           | Not classified   |
| Xylene, Mixture of Isomers                  | (CAS No) 1330-20-7  | < 1           | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315  |
| Ethylbenzene                                | (CAS No) 100-41-4   | < 1           | Flam. Liq. 2, H225<br>Acute Tox. 4 (Inhalation:vapour),<br>H332<br>Carc. 2, H351<br>STOT RE 2, H373<br>Asp. Tox. 1, H304 |

The exact percentage is a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer.
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : If you feel unwell, seek medical advice. May cause genetic defects. May cause cancer.
- Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Symptoms/injuries after skin contact : May cause slight irritation . Itching. Red skin.
- Symptoms/injuries after eye contact : Irritation of the eye tissue. May cause slight eye irritation . Redness of the eye tissue. Inflammation/damage of the eye tissue.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.

# JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash affected areas thoroughly after handling. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Ethylbenzene (100-41-4) |                                      |                       |
|-------------------------|--------------------------------------|-----------------------|
| USA ACGIH               | ACGIH TWA (ppm)                      | 100 ppm               |
| USA ACGIH               | ACGIH STEL (ppm)                     | 125 ppm               |
| USA OSHA                | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 435 mg/m <sup>3</sup> |
| USA OSHA                | OSHA PEL (TWA) (ppm)                 | 100                   |
| USA OSHA                | OSHA PEL (STEL) (mg/m <sup>3</sup> ) | 545 mg/m <sup>3</sup> |
| USA OSHA                | OSHA PEL (STEL) (ppm)                | 125 ppm               |

| Distillates (Petroleum), Hydrotreated Light (64742-47-8) |                 |                 |
|--|-----------------|-----------------|
| USA ACGIH  | ACGIH TWA (ppm) | 200 ppm 8 Hours |

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods. Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Materials for protective clothing : GIVE EXCELLENT RESISTANCE:

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear respiratory protection.

Environmental exposure controls : Avoid release to the environment.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Liquid.

# JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |                                   |
|---|-----------------------------------|
| Color                                       | : Colourless to light yellow.     |
| Odor  | : Petroleum-like odour.           |
| Odor threshold                              | : No data available               |
| pH  | : No data available               |
| Relative evaporation rate (butyl acetate=1) | : No data available               |
| Melting point                               | : No data available               |
| Freezing point                              | : No data available               |
| Boiling point                               | : 187 - 264 °C (Lowest Component) |
| Flash point                                 | : 86 °C                           |
| Auto-ignition temperature                   | : No data available               |
| Decomposition temperature                   | : No data available               |
| Flammability (solid, gas)                   | : No data available               |
| Vapor pressure                              | : No data available               |
| Relative vapor density at 20 °C             | : No data available               |
| Relative density                            | : 0.79                            |
| Solubility                                  | : Poorly soluble in water.        |
| Log Pow                                     | : No data available               |
| Log Kow                                     | : No data available               |
| Viscosity, kinematic                        | : 1.7 cSt @ 40 deg C              |
| Viscosity, dynamic                          | : No data available               |
| Explosive properties                        | : No data available               |
| Oxidizing properties                        | : No data available               |
| Explosion limits                            | : No data available               |

### 9.2. Other information

VOC content : 1.7 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

| <b>Ethylbenzene (100-41-4)</b>                                  |  |
|---|--|
| LD50 oral rat   | 3500 mg/kg (Rat; Other; Experimental value)  |
| LD50 dermal rabbit  | 15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value) |
| LC50 inhalation rat (mg/l)                                      | 17.8 mg/l/4h (Rat; Literature study)   |
| LC50 inhalation rat (ppm)                                       | 4000 ppm/4h (Rat; Literature study)  |
| <b>Paraffins (Petroleum), Normal C5-20 (64771-72-8)</b>         |  |
| LD50 oral rat   | > 5000 mg/kg (Rat)   |
| LD50 dermal rabbit  | > 2000 mg/kg (Rabbit)  |
| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b> |  |
| LD50 oral rat   | > 5000 mg/kg body weight   |
| LD50 dermal rabbit  | > 2000 mg/kg   |
| LC50 inhalation rat (mg/l)                                      | > 5.28 mg/l/4h Based on lack of mortality and systemic effects                         |

# JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Xylene, Mixture of Isomers (1330-20-7)</b> |   |
|---|---|
| LD50 oral rat                                 | 3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value) |
| LD50 dermal rabbit                            | > 4200 mg/kg (Rabbit; Experimental value,Rabbit; Experimental value)  |
| LC50 inhalation rat (mg/l)                    | 29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)  |

|                                   |                                |
|-----------------------------------|--------------------------------|
| Skin corrosion/irritation         | : Not classified               |
| Serious eye damage/irritation     | : Not classified               |
| Respiratory or skin sensitization | : Not classified               |
| Germ cell mutagenicity            | : Not classified               |
| Carcinogenicity                   | : Suspected of causing cancer. |

| <b>Ethylbenzene (100-41-4)</b> |    |
|--------------------------------|----|
| IARC group                     | 2B |

| <b>Xylene, Mixture of Isomers (1330-20-7)</b> |   |
|---|---|
| IARC group                                    | 3 |

|   |   |
|---|---|
| Reproductive toxicity                               | : Not classified  |
| Specific target organ toxicity – single exposure    | : Not classified  |
| Specific target organ toxicity – repeated exposure  | : Not classified  |
| Aspiration hazard                                   | : May be fatal if swallowed and enters airways.   |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met.   |
| Symptoms/injuries after inhalation                  | : May cause allergy or asthma symptoms or breathing difficulties if inhaled.  |
| Symptoms/injuries after skin contact                | : May cause slight irritation . Itching. Red skin.  |
| Symptoms/injuries after eye contact                 | : Irritation of the eye tissue. May cause slight eye irritation . Redness of the eye tissue. Inflammation/damage of the eye tissue. |
| Symptoms/injuries after ingestion                   | : May be fatal if swallowed and enters airways.   |

## SECTION 12: Ecological information

### 12.1. Toxicity

| <b>Ethylbenzene (100-41-4)</b> |  |
|--------------------------------|--|
| LC50 fish 2                    | 4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value) |

### 12.2. Persistence and degradability

| <b>JOHNSEN'S CARB &amp; FUEL INJECTOR CLEANER 6 FL.OZ.</b> |                  |
|--|------------------|
| Persistence and degradability                              | Not established. |

| <b>Ethylbenzene (100-41-4)</b>  |  |
|---------------------------------|--|
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil. |
| Biochemical oxygen demand (BOD) | 1.44 g O <sub>2</sub> /g substance (20d.)  |
| Chemical oxygen demand (COD)    | 2.1 g O <sub>2</sub> /g substance  |
| ThOD                            | 3.17 g O <sub>2</sub> /g substance   |
| BOD (% of ThOD)                 | 45.4 (20 days)   |

| <b>Paraffins (Petroleum), Normal C5-20 (64771-72-8)</b> |                                 |
|---|---------------------------------|
| Persistence and degradability                           | Readily biodegradable in water. |

| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b> |                  |
|---|------------------|
| Persistence and degradability                                   | Not established. |

| <b>Xylene, Mixture of Isomers (1330-20-7)</b> |   |
|---|---|
| Persistence and degradability                 | Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air. |

| <b>Naphtha, Hydrotreated Heavy (64742-48-9)</b> |                  |
|---|------------------|
| Persistence and degradability                   | Not established. |

### 12.3. Bioaccumulative potential

| <b>JOHNSEN'S CARB &amp; FUEL INJECTOR CLEANER 6 FL.OZ.</b> |                  |
|--|------------------|
| Bioaccumulative potential                                  | Not established. |

| <b>Ethylbenzene (100-41-4)</b> |  |
|--------------------------------|--|
| BCF fish 1                     | 1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study) |

# JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Ethylbenzene (100-41-4)</b> |   |
|--------------------------------|---|
| BCF fish 2                     | 15 - 79 (BCF)   |
| BCF other aquatic organisms 1  | 4.68 (BCF)  |
| Log Pow                        | 3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C) |
| Bioaccumulative potential      | Low potential for bioaccumulation (BCF < 500).  |

| <b>Paraffins (Petroleum), Normal C5-20 (64771-72-8)</b> |                                    |
|---|------------------------------------|
| Bioaccumulative potential                               | No bioaccumulation data available. |

| <b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b> |                  |
|---|------------------|
| Bioaccumulative potential                                       | Not established. |

| <b>Xylene, Mixture of Isomers (1330-20-7)</b> |  |
|---|--|
| BCF fish 2                                    | 7 - 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water) |
| Log Pow                                       | 3.2 (Conclusion by analogy; 20 °C)   |
| Bioaccumulative potential                     | Low potential for bioaccumulation (BCF < 500).                               |

| <b>Naphtha, Hydrotreated Heavy (64742-48-9)</b> |                  |
|---|------------------|
| Bioaccumulative potential                       | Not established. |

### 12.4. Mobility in soil

| <b>Ethylbenzene (100-41-4)</b> |  |
|--------------------------------|--|
| Surface tension                | 0.029 N/m  |
| Log Koc                        | log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value |

| <b>Xylene, Mixture of Isomers (1330-20-7)</b> |   |
|---|---|
| Ecology - soil                                | May be harmful to plant growth, blooming and fruit formation. |

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not Regulated,

ICAO/IATA (air): Not regulated,

IMO/IMDG (water): Not regulated,

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not Regulated

### 14.3. Additional information

Other information : No supplementary information available.

### Overland transport

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

# JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

|                                     |   |
|-------------------------------------|---|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard<br>Fire hazard<br>Immediate (acute) health hazard |
|-------------------------------------|---|

##### Ethylbenzene (100-41-4)

|  |   |
|--|---|
| Subject to reporting requirements of United States SARA Section 313<br>Listed on the United States TSCA (Toxic Substances Control Act) inventory |   |
| SARA Section 311/312 Hazard Classes  | Immediate (acute) health hazard<br>Fire hazard<br>Delayed (chronic) health hazard |

##### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

|                                     |  |
|-------------------------------------|--|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard<br>Delayed (chronic) health hazard |
|-------------------------------------|--|

##### Xylene, Mixture of Isomers (1330-20-7)

|                                     |             |
|-------------------------------------|-------------|
| SARA Section 311/312 Hazard Classes | Fire hazard |
|-------------------------------------|-------------|

#### 15.2. International regulations

##### CANADA

##### JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

|                      |   |
|----------------------|---|
| WHMIS Classification | Class B Division 3 - Combustible Liquid |
|----------------------|---|

##### Ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

##### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

|                      |   |
|----------------------|---|
| WHMIS Classification | Uncontrolled product according to WHMIS classification criteria |
|----------------------|---|

##### Distillates, Hydrotreated Light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

|                      |                                       |
|----------------------|---------------------------------------|
| WHMIS Classification | Class B Division 2 - Flammable Liquid |
|----------------------|---------------------------------------|

#### EU-Regulations

No additional information available

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

Muta.Cat.2; R46

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

##### Ethylbenzene (100-41-4)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECI (Korean Existing Chemicals Inventory)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

#### 15.3. US State regulations

##### JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

|   |                                    |
|---|------------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List               | No                                 |
| U.S. - California - Proposition 65 - Developmental Toxicity         | No                                 |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No                                 |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male   | No                                 |
| State or local regulations  | U.S. - California - Proposition 65 |



# JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Ethylbenzene (100-41-4)                               |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| Yes   | No  | No  | No  |                                   |

| Paraffins (Petroleum), Normal C5-20 (64771-72-8)      |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No  | No  |                                   |

| Distillates (Petroleum), Hydrotreated Light (64742-47-8) |   |   |   |                                   |
|--|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List    | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No   | No  | No  | No  |                                   |

| Xylene, Mixture of Isomers (1330-20-7)                |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No  | No  |                                   |

| Distillates, Hydrotreated Light (64742-47-8)          |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No  | No  |                                   |

| Naphtha, Hydrotreated Heavy (64742-48-9)              |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| No  | No  | No  | No  |                                   |

| Ethylbenzene (100-41-4)                                    |  |  |  |  |
|--|--|--|--|--|
| State or local regulations                                 |  |  |  |  |
| U.S. - Pennsylvania - RTK (Right to Know) List             |  |  |  |  |
| U.S. - New Jersey - Right to Know Hazardous Substance List |  |  |  |  |
| U.S. - California - Proposition 65                         |  |  |  |  |

## SECTION 16: Other information

Other information : None.

Full text of H-phrases:


|      |   |
|------|---|
| H225 | Highly flammable liquid and vapor                                 |
| H226 | Flammable liquid and vapor  |
| H227 | Combustible liquid  |
| H304 | May be fatal if swallowed and enters airways                      |
| H315 | Causes skin irritation  |
| H332 | Harmful if inhaled  |
| H351 | Suspected of causing cancer                                       |
| H373 | May cause damage to organs through prolonged or repeated exposure |

NFPA health hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.





# JOHNSEN'S CARB & FUEL INJECTOR CLEANER 6 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,  
and are not reactive with water.

### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur  
Flammability : 2 Moderate Hazard  
Physical : 0 Minimal Hazard  
Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*