



# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 10/23/2014

Version:

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON  
Product code : 2456

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Brake Parts Cleaner

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

|                                     |      |
|-------------------------------------|------|
| Flam. Liq. 2                        | H225 |
| Acute Tox. 3 (Oral)                 | H301 |
| Acute Tox. 3 (Dermal)               | H311 |
| Acute Tox. 4 (Inhalation:dust,mist) | H332 |
| Skin Irrit. 2                       | H315 |
| Eye Irrit. 2A                       | H319 |
| Repr. 2                             | H361 |
| STOT SE 3                           | H336 |
| STOT SE 1                           | H370 |
| STOT RE 2                           | H373 |

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS06

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor  
H301+H311 - Toxic if swallowed or in contact with skin  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H336 - May cause drowsiness or dizziness  
H361 - Suspected of damaging fertility or the unborn child  
H370 - Causes damage to organs  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, ventilating, lighting equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe dust, fumes, gas, mist, vapor spray  
P261 - Avoid breathing dust, fume, gas, mist, vapor spray  
P264 - Wash affected areas thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves, protective clothing, eye protection, face protection

# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,  
P302+P352 - If on skin: Wash with plenty of soap and water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P307+P311 - If exposed: Call a poison center/doctor  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.  
P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment: See section 4.1 on SDS  
P330 - Rinse mouth  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P361 - Take off immediately all contaminated clothing  
P362 - Take off contaminated clothing and wash before reuse  
P363 - Wash contaminated clothing before reuse  
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS-US)

No data available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name     | Product identifier | %       | Classification (GHS-US)  |
|----------|--------------------|---------|--|
| Acetone  | (CAS No) 67-64-1   | 50 - 70 | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336   |
| Methanol | (CAS No) 67-56-1   | 10 - 30 | Flam. Liq. 2, H225<br>Acute Tox. 3 (Oral), H301<br>Acute Tox. 3 (Dermal), H311<br>Acute Tox. 3 (Inhalation:dust,mist), H331<br>STOT SE 1, H370 |
| Toluene  | (CAS No) 108-88-3  | 10 - 30 | Flam. Liq. 2, H225<br>Skin Irrit. 2, H315<br>Repr. 2, H361<br>STOT SE 3, H336<br>STOT RE 2, H373<br>Asp. Tox. 1, H304                          |

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a POISON CENTER or doctor/physician. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.

# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                     |  |
|-------------------------------------|--|
| Symptoms/injuries after eye contact | : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.        |
| Symptoms/injuries after ingestion   | : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard. |

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

|                                |  |
|--------------------------------|--|
| Suitable extinguishing media   | : Foam. Dry powder. Carbon dioxide. Water spray. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                     |

### 5.2. Special hazards arising from the substance or mixture

|                  |   |
|------------------|---|
| Fire hazard      | : Highly flammable liquid and vapor.              |
| Explosion hazard | : May form flammable/explosive vapor-air mixture. |

### 5.3. Advice for firefighters

|                                |   |
|--------------------------------|---|
| Firefighting instructions      | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection.   |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |  |
|------------------|--|
| General measures | : Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking. |
|------------------|--|

#### 6.1.1. For non-emergency personnel

|                      |                                   |
|----------------------|-----------------------------------|
| Protective equipment | : Gloves. Safety glasses.         |
| Emergency procedures | : Evacuate unnecessary personnel. |

#### 6.1.2. For emergency responders

|                      |  |
|----------------------|--|
| Protective equipment | : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray. |
| Emergency procedures | : Ventilate area.  |

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

|                         |  |
|-------------------------|--|
| For containment         | : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.                       |
| Methods for cleaning up | : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. |

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

|                                   |   |
|-----------------------------------|---|
| Additional hazards when processed | : Handle empty containers with care because residual vapors are flammable.  |
| Precautions for safe handling     | : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No naked lights. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust,fume,gas,mist,vapor spray. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Do not breathe dust,fumes,gas,mist,vapor spray. |
| Hygiene measures                  | : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.   |

### 7.2. Conditions for safe storage, including any incompatibilities

|                        |   |
|------------------------|---|
| Technical measures     | : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment. |
| Storage conditions     | : Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof place. Keep container tightly closed.  |
| Incompatible products  | : Strong bases. Strong acids.   |
| Incompatible materials | : Sources of ignition. Direct sunlight. Heat sources.   |

### 7.3. Specific end use(s)

Follow Label Directions.

# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| Toluene (108-88-3) |                                |                      |
|--------------------|--------------------------------|----------------------|
| USA ACGIH          | ACGIH TWA (mg/m <sup>3</sup> ) | 75 mg/m <sup>3</sup> |
| USA ACGIH          | ACGIH TWA (ppm)                | 20 ppm               |
| USA OSHA           | OSHA PEL (TWA) (ppm)           | 200 ppm              |
| USA OSHA           | OSHA PEL (Ceiling) (ppm)       | 300 ppm              |

| Benzene (71-43-2) |                          |        |
|-------------------|--------------------------|--------|
| USA ACGIH         | ACGIH TWA (ppm)          | 1 ppm  |
| USA ACGIH         | ACGIH STEL (ppm)         | 5 ppm  |
| USA ACGIH         | ACGIH Ceiling (ppm)      | 25 ppm |
| USA OSHA          | OSHA PEL (TWA) (ppm)     | 1 ppm  |
| USA OSHA          | OSHA PEL (Ceiling) (ppm) | 5 ppm  |

| Methanol (67-56-1) |                                     |                       |
|--------------------|-------------------------------------|-----------------------|
| USA ACGIH          | ACGIH TWA (mg/m <sup>3</sup> )      | 262 mg/m <sup>3</sup> |
| USA ACGIH          | ACGIH TWA (ppm)                     | 200 ppm               |
| USA ACGIH          | ACGIH STEL (mg/m <sup>3</sup> )     | 328 mg/m <sup>3</sup> |
| USA ACGIH          | ACGIH STEL (ppm)                    | 250 ppm               |
| USA OSHA           | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 260 mg/m <sup>3</sup> |
| USA OSHA           | OSHA PEL (TWA) (ppm)                | 200 ppm               |

| Acetone (67-64-1) |                                     |                        |
|-------------------|-------------------------------------|------------------------|
| USA ACGIH         | ACGIH TWA (mg/m <sup>3</sup> )      | 1188 mg/m <sup>3</sup> |
| USA ACGIH         | ACGIH TWA (ppm)                     | 500 ppm                |
| USA ACGIH         | ACGIH STEL (mg/m <sup>3</sup> )     | 1782 mg/m <sup>3</sup> |
| USA ACGIH         | ACGIH STEL (ppm)                    | 750 ppm                |
| USA OSHA          | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 2400 mg/m <sup>3</sup> |
| USA OSHA          | OSHA PEL (TWA) (ppm)                | 1000 ppm               |

#### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods.  
Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.  
Eye protection : Chemical goggles or safety glasses.  
Skin and body protection : Wear suitable protective clothing.  
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.  
Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Color : Colourless to light yellow.  
Odor : Solvent-like odour.  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available

# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                 |                             |
|---------------------------------|-----------------------------|
| Melting point                   | : No data available         |
| Freezing point                  | : No data available         |
| Boiling point                   | : 56 °C (Lowest Component)  |
| Flash point                     | : -18 °C (Lowest Component) |
| Auto-ignition temperature       | : 465 °C (Lowest Component) |
| Decomposition temperature       | : No data available         |
| Flammability (solid, gas)       | : No data available         |
| Vapor pressure                  | : No data available         |
| Relative vapor density at 20 °C | : No data available         |
| Relative density                | : 0.86                      |
| Solubility                      | : Poorly soluble in water.  |
| Log Pow                         | : No data available         |
| Log Kow                         | : No data available         |
| Viscosity, kinematic            | : No data available         |
| Viscosity, dynamic              | : No data available         |
| Explosive properties            | : No data available         |
| Oxidizing properties            | : No data available         |
| Explosive limits                | : No data available         |

### 9.2. Other information

VOC content : 44.9 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Toxic if swallowed. Toxic in contact with skin. Harmful if inhaled.

| <b>Toluene (108-88-3)</b>  |   |
|----------------------------|---|
| LD50 oral rat              | 5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value) |
| LD50 dermal rabbit         | > 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)  |
| LC50 inhalation rat (mg/l) | > 28.1 mg/l/4h (Rat; Air, Literature study)   |
| <b>Benzene (71-43-2)</b>   |   |
| LD50 oral rat              | > 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg bodyweight; Rat; Experimental value)          |
| LD50 dermal rabbit         | > 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)   |
| LC50 inhalation rat (mg/l) | 43.767 mg/l/4h (Rat; Experimental value)  |
| LC50 inhalation rat (ppm)  | 13700 ppm/4h (Rat; Experimental value)  |
| <b>Methanol (67-56-1)</b>  |   |
| LD50 oral rat              | >= 2528 mg/kg body weight application as 50% aqueous solution   |
| LD50 dermal rabbit         | 17100 mg/kg corresponding to 20 ml/kg bw according to the authors   |
| LC50 inhalation rat (mg/l) | 128.2 mg/l/4h Air   |
| <b>Acetone (67-64-1)</b>   |   |
| LD50 oral rat              | 5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)   |

# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Acetone (67-64-1)</b>   |   |
|----------------------------|---|
| LD50 dermal rabbit         | 20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402) |
| LC50 inhalation rat (mg/l) | 71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)   |
| LC50 inhalation rat (ppm)  | 30000 ppm/4h (Rat; Experimental value)                                      |

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

| <b>Toluene (108-88-3)</b> |   |
|---------------------------|---|
| IARC group                | 3 |

| <b>Benzene (71-43-2)</b> |   |
|--------------------------|---|
| IARC group               | 1 |

Reproductive toxicity : Suspected of damaging fertility or the unborn child.  
Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness. Causes damage to organs.  
Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.  
Aspiration hazard : Not classified  
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met. Harmful if inhaled. Toxic if swallowed. Toxic in contact with skin.  
Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled. May cause drowsiness or dizziness.  
Symptoms/injuries after skin contact : Repeated exposure to this material can result in absorption through skin causing significant health hazard. Toxic in contact with skin. Causes skin irritation.  
Symptoms/injuries after eye contact : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.  
Symptoms/injuries after ingestion : Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

## SECTION 12: Ecological information

### 12.1. Toxicity

| <b>Toluene (108-88-3)</b> |   |
|---------------------------|---|
| LC50 fish 1               | 24 mg/l 96 h; <i>Salmo gairdneri</i> ( <i>Oncorhynchus mykiss</i> ) |
| EC50 Daphnia 1            | 84 mg/l (24 h; <i>Daphnia magna</i> ; Locomotor effect)             |
| LC50 fish 2               | 13 mg/l (96 h; <i>Lepomis macrochirus</i> )                         |
| EC50 Daphnia 2            | 11.5 - 19.6 mg/l (48 h; <i>Daphnia magna</i> )                      |
| Threshold limit algae 1   | > 400 mg/l (168 h; <i>Scenedesmus quadricauda</i> ; Toxicity test)  |
| Threshold limit algae 2   | 105 mg/l (192 h; <i>Microcystis aeruginosa</i> )                    |

| <b>Benzene (71-43-2)</b>       |  |
|--------------------------------|--|
| LC50 fish 1                    | 5.3 mg/l 96 h; <i>Salmo gairdneri</i> ( <i>Oncorhynchus mykiss</i> ) |
| EC50 Daphnia 1                 | 18 mg/l (24 h; <i>Daphnia magna</i> )                                |
| EC50 other aquatic organisms 1 | 29 mg/l (72 h; <i>Selenastrum capricornutum</i> )                    |
| LC50 fish 2                    | 15.1 mg/l (96 h; <i>Pimephales promelas</i> )                        |
| EC50 Daphnia 2                 | 10 mg/l (48 h; <i>Daphnia magna</i> )                                |
| TLM fish 1                     | 22.5 mg/l (96 h; <i>Lepomis macrochirus</i> ; Soft water)            |
| TLM fish 2                     | 32 mg/l (96 h; <i>Pimephales promelas</i> ; Hard water)              |
| TLM other aquatic organisms 1  | 10 - 100,96 h  |
| Threshold limit algae 2        | 50 mg/l (24 h; <i>Phaeodactylum</i> ; Photosynthesis)                |

| <b>Acetone (67-64-1)</b>                  |   |
|---|---|
| TLM fish 1                                | 13000 ppm (96 h; <i>Gambusia affinis</i> ; Turbulent water) |
| TLM fish 2                                | > 1000 ppm (96 h; Pisces)                                   |
| Threshold limit other aquatic organisms 1 | 3000 mg/l (Plankton)  |
| Threshold limit other aquatic organisms 2 | 28 mg/l (Protozoa)  |
| Threshold limit algae 1                   | 7500 mg/l ( <i>Scenedesmus quadricauda</i> ; pH = 7)        |
| Threshold limit algae 2                   | 3400 mg/l (48 h; <i>Chlorella sp.</i> )                     |

| <b>Methanol (67-56-1)</b> |  |
|---------------------------|--|
| LC50 fish 1               | 15400 mg/l (96 h; <i>Lepomis macrochirus</i> ; Lethal) |
| EC50 Daphnia 1            | > 10000 mg/l (48 h; <i>Daphnia magna</i> ; Lethal)     |

# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Methanol (67-56-1)</b>                 |  |
|---|--|
| LC50 fish 2                               | 10800 mg/l 96 h; <i>Salmo gairdneri</i> ( <i>Oncorhynchus mykiss</i> ) |
| EC50 Daphnia 2                            | 24500 mg/l (48 h; <i>Daphnia magna</i> )                               |
| Threshold limit other aquatic organisms 1 | 6600 mg/l (16 h; <i>Pseudomonas putida</i> )                           |
| Threshold limit algae 1                   | 530 mg/l (192 h; <i>Microcystis aeruginosa</i> )                       |
| Threshold limit algae 2                   | 8000 mg/l (168 h; <i>Scenedesmus quadricauda</i> )                     |

| <b>Acetone (67-64-1)</b>                  |   |
|---|---|
| LC50 fish 1                               | 6210 mg/l (96 h; <i>Pimephales promelas</i> ; Nominal concentration)  |
| EC50 Daphnia 1                            | 8800 mg/l (48 h; <i>Daphnia pulex</i> )                               |
| LC50 fish 2                               | 5540 mg/l 96 h; <i>Salmo gairdneri</i> ( <i>Oncorhynchus mykiss</i> ) |
| TLM fish 1                                | 13000 ppm (96 h; <i>Gambusia affinis</i> ; Turbulent water)           |
| TLM fish 2                                | > 1000 ppm (96 h; Pisces)   |
| Threshold limit other aquatic organisms 1 | 3000 mg/l (Plankton)  |
| Threshold limit other aquatic organisms 2 | 28 mg/l (Protozoa)  |
| Threshold limit algae 1                   | 7500 mg/l ( <i>Scenedesmus quadricauda</i> ; pH = 7)                  |
| Threshold limit algae 2                   | 3400 mg/l (48 h; <i>Chlorella sp.</i> )                               |

### 12.2. Persistence and degradability

| <b>JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON</b> |                  |
|---|------------------|
| Persistence and degradability                               | Not established. |

| <b>Toluene (108-88-3)</b>       |  |
|---------------------------------|--|
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil. |
| Biochemical oxygen demand (BOD) | 2.15 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)    | 2.52 g O <sub>2</sub> /g substance   |
| ThOD                            | 3.13 g O <sub>2</sub> /g substance   |
| BOD (% of ThOD)                 | 0.69 % ThOD  |

| <b>Benzene (71-43-2)</b>        |   |
|---------------------------------|---|
| Persistence and degradability   | Biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Photolysis in the air. |
| Biochemical oxygen demand (BOD) | 2.18 g O <sub>2</sub> /g substance  |
| Chemical oxygen demand (COD)    | 2.15 g O <sub>2</sub> /g substance  |
| ThOD                            | 3.10 g O <sub>2</sub> /g substance  |
| BOD (% of ThOD)                 | 0.70 % ThOD   |

| <b>Acetone (67-64-1)</b>      |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

| <b>Methanol (67-56-1)</b>       |  |
|---------------------------------|--|
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. |
| Biochemical oxygen demand (BOD) | 0.6 - 1.12 g O <sub>2</sub> /g substance                   |
| Chemical oxygen demand (COD)    | 1.42 g O <sub>2</sub> /g substance                         |
| ThOD                            | 1.5 g O <sub>2</sub> /g substance                          |
| BOD (% of ThOD)                 | 0.8 % ThOD   |

| <b>Acetone (67-64-1)</b>        |   |
|---------------------------------|---|
| Persistence and degradability   | Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established. |
| Biochemical oxygen demand (BOD) | 1.43 g O <sub>2</sub> /g substance  |
| Chemical oxygen demand (COD)    | 1.92 g O <sub>2</sub> /g substance  |
| ThOD                            | 2.20 g O <sub>2</sub> /g substance  |
| BOD (% of ThOD)                 | (20 day(s)) 0.872   |

### 12.3. Bioaccumulative potential

| <b>JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON</b> |                  |
|---|------------------|
| Bioaccumulative potential                                   | Not established. |

| <b>Toluene (108-88-3)</b>     |   |
|-------------------------------|---|
| BCF fish 1                    | 13.2 ( <i>Anguilla japonica</i> )               |
| BCF fish 2                    | 90 (72 h; <i>Leuciscus idus</i> )               |
| BCF other aquatic organisms 1 | 380 (24 h; <i>Chlorella sp.</i> ; Fresh weight) |
| BCF other aquatic organisms 2 | 4.2 ( <i>Mytilus edulis</i> ; Fresh weight)     |
| Log Pow                       | 2.73 (Experimental value; Other; 20 °C)         |



# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Toluene (108-88-3)</b> |  |
|---------------------------|--|
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

| <b>Benzene (71-43-2)</b>      |  |
|-------------------------------|--|
| BCF fish 1                    | 19 <i>Salmo gairdneri</i> ( <i>Oncorhynchus mykiss</i> ) |
| BCF other aquatic organisms 1 | 30 (24 h; <i>Chlorella</i> sp.; Fresh weight)            |
| Log Pow                       | 2.13 (Experimental value)                                |
| Bioaccumulative potential     | Low potential for bioaccumulation (BCF < 500).           |

| <b>Acetone (67-64-1)</b>  |                  |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

| <b>Methanol (67-56-1)</b> |  |
|---------------------------|--|
| BCF fish 1                | < 10 ( <i>Leuciscus idus</i> )                 |
| Log Pow                   | -0.77 (Experimental value; Other)              |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

| <b>Acetone (67-64-1)</b>      |                                       |
|-------------------------------|---------------------------------------|
| BCF fish 1                    | 0.69 (Pisces)                         |
| BCF other aquatic organisms 1 | 3                                     |
| Log Pow                       | -0.24 (Test data)                     |
| Bioaccumulative potential     | Not bioaccumulative. Not established. |

### 12.4. Mobility in soil

| <b>Toluene (108-88-3)</b> |                  |
|---------------------------|------------------|
| Surface tension           | 0.03 N/m (20 °C) |

| <b>Benzene (71-43-2)</b> |                   |
|--------------------------|-------------------|
| Surface tension          | 0.029 N/m (20 °C) |

| <b>Methanol (67-56-1)</b> |                   |
|---------------------------|-------------------|
| Surface tension           | 0.023 N/m (20 °C) |

| <b>Acetone (67-64-1)</b> |                    |
|--------------------------|--------------------|
| Surface tension          | 0.0237 N/m (20 °C) |

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.



# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

|                     |  |
|---------------------|--|
| US DOT (ground):    | UN1993, Flammable liquids, n.o.s. (Acetone, Methanol, Toluene), 3, II  |
| ICAO/IATA (air):    | UN1993, Flammable liquids, n.o.s. (Acetone, Methanol, Toluene), 3, II  |
| IMO/IMDG (water):   | UN1993, Flammable liquids, n.o.s. (Acetone, Methanol, Toluene), 3, II  |
| Special Provisions: | IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.<br>T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)<br>TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.<br>TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).<br>TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP. |

#### 14.2. UN proper shipping name

|   |   |
|---|---|
| Proper Shipping Name (DOT)                        | : Flammable liquids, n.o.s. (Acetone, Methanol, Toluene)        |
| Department of Transportation (DOT) Hazard Classes | : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120 |
| Hazard labels (DOT)                               | : 3 - Flammable liquid  |



|   |  |
|---|--|
| DOT Symbols                               | : G - Identifies PSN requiring a technical name  |
| Packing group (DOT)                       | : II - Medium Danger   |
| DOT Special Provisions (49 CFR 172.102)   | : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.<br>T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)<br>TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.<br>TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).<br>TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP. |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 150  |
| DOT Packaging Non Bulk (49 CFR 173.xxx)   | : 202  |
| DOT Packaging Bulk (49 CFR 173.xxx)       | : 242  |

#### 14.3. Additional information

|                   |   |
|-------------------|---|
| Other information | : No supplementary information available. |
|-------------------|---|

#### Overland transport

No additional information available

#### Transport by sea

|                             |   |
|-----------------------------|---|
| DOT Vessel Stowage Location | : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded. |
|-----------------------------|---|

#### Air transport

|  |        |
|--|--------|
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 5 L  |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)     | : 60 L |

# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

|                                     |   |
|-------------------------------------|---|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard<br>Fire hazard<br>Immediate (acute) health hazard |
|-------------------------------------|---|

##### Toluene (108-88-3)

|   |   |
|---|---|
| Listed on United States SARA Section 313<br>Listed on the United States TSCA (Toxic Substances Control Act) inventory |   |
| SARA Section 311/312 Hazard Classes   | Delayed (chronic) health hazard<br>Fire hazard<br>Immediate (acute) health hazard |

##### Methanol (67-56-1)

|   |   |
|---|---|
| Listed on United States SARA Section 313<br>Listed on the United States TSCA (Toxic Substances Control Act) inventory |   |
| SARA Section 311/312 Hazard Classes   | Immediate (acute) health hazard<br>Delayed (chronic) health hazard<br>Fire hazard |

##### Acetone (67-64-1)

|   |   |
|---|---|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory |   |
| SARA Section 311/312 Hazard Classes                                       | Immediate (acute) health hazard<br>Fire hazard<br>Delayed (chronic) health hazard |

#### 15.2. International regulations

##### CANADA

##### JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

|                      |                                       |
|----------------------|---------------------------------------|
| WHMIS Classification | Class B Division 2 - Flammable Liquid |
|----------------------|---------------------------------------|

##### Toluene (108-88-3)

|                      |   |
|----------------------|---|
| WHMIS Classification | Class B Division 2 - Flammable Liquid<br>Class D Division 2 Subdivision A - Very toxic material causing other toxic effects |
|----------------------|---|

##### Methanol (67-56-1)

|                      |   |
|----------------------|---|
| WHMIS Classification | Class B Division 2 - Flammable Liquid<br>Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects<br>Class D Division 2 Subdivision A - Very toxic material causing other toxic effects<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
|----------------------|---|

##### Acetone (67-64-1)

|   |  |
|---|--|
| Listed on the Canadian DSL (Domestic Substances List) |  |
| WHMIS Classification                                  | Class B Division 2 - Flammable Liquid<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects |

#### EU-Regulations

##### Toluene (108-88-3)

|  |  |
|--|--|
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) |  |
|--|--|

##### Acetone (67-64-1)

|  |  |
|--|--|
| Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)<br>Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) |  |
|--|--|

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Repr.Cat.3; R63  
F; R11  
T; R23/24/25  
T; R39/23/24/25  
Xn; R48/20  
Xi; R36/38

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Acetone (67-64-1)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on KECI (Korean Existing Chemicals Inventory)  
 Listed on AICS (Australian Inventory of Chemical Substances)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on the Korean ECL (Existing Chemicals List)

### 15.3. US State regulations

#### JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

State or local regulations U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

### Acetone (67-64-1)

|   |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significance risk level (NSRL) |
| Yes   |   |   |   |                                   |

### Toluene (108-88-3)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

### Acetone (67-64-1)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)  
 Benzene 71-43-2  
 U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information


Other information : None.

Full text of H-phrases: see section 16:

|                                     |   |
|-------------------------------------|---|
| Acute Tox. 3 (Dermal)               | Acute toxicity (dermal) Category 3                                |
| Acute Tox. 3 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 3                  |
| Acute Tox. 3 (Oral)                 | Acute toxicity (oral) Category 3                                  |
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4                  |
| Asp. Tox. 1                         | Aspiration hazard Category 1                                      |
| Eye Irrit. 2A                       | Serious eye damage/eye irritation Category 2A                     |
| Flam. Liq. 2                        | Flammable liquids Category 2                                      |
| Repr. 2                             | Reproductive toxicity Category 2                                  |
| Skin Irrit. 2                       | Skin corrosion/irritation Category 2                              |
| STOT RE 2                           | Specific target organ toxicity (repeated exposure) Category 2     |
| STOT SE 1                           | Specific target organ toxicity (single exposure) Category 1       |
| STOT SE 3                           | Specific target organ toxicity (single exposure) Category 3       |
| H225                                | Highly flammable liquid and vapor                                 |
| H301                                | Toxic if swallowed  |
| H304                                | May be fatal if swallowed and enters airways                      |
| H311                                | Toxic in contact with skin  |
| H315                                | Causes skin irritation  |
| H319                                | Causes serious eye irritation                                     |
| H331                                | Toxic if inhaled  |
| H332                                | Harmful if inhaled  |
| H336                                | May cause drowsiness or dizziness                                 |
| H361                                | Suspected of damaging fertility or the unborn child               |
| H370                                | Causes damage to organs   |
| H373                                | May cause damage to organs through prolonged or repeated exposure |

NFPA health hazard

: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.



# JOHNSEN'S NON-CHLORINATED BPC 45% VOC DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

|                  |  |
|------------------|--|
| NFPA fire hazard | : 3 - Liquids and solids that can be ignited under almost all ambient conditions.            |
| NFPA reactivity  | : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water. |

### HMIS III Rating

|                     |   |
|---------------------|---|
| Health              | : 2 Moderate Hazard - Temporary or minor injury may occur |
| Flammability        | : 3 Serious Hazard  |
| Physical            | : 0 Minimal Hazard  |
| Personal Protection | : B   |

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*