



JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/03/2014

Version:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Trade name : JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM
CAS No : 64742-47-8
Product code : 4609-55

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine Flush

1.3. Details of the supplier of the safety data sheet

Technical Chemical Company
P.O. BOX 139
Cleburne, Texas 76033
T 817-645-6088

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Asp. Tox. 1 H304

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H304 - May be fatal if swallowed and enters airways
Precautionary statements (GHS-US) : P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,
P331 - Do NOT induce vomiting
P405 - Store locked up
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Name : Distillates (Petroleum), Hydrotreated Light
CAS No : 64742-47-8

Name	Product identifier	%	Classification (GHS-US)
Distillates (Petroleum), Hydrotreated Light (Main constituent)	(CAS No) 64742-47-8	> 95	Asp. Tox. 1, H304

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after inhalation	: Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: If you feel unwell, seek medical advice.
Symptoms/injuries after inhalation	: Dizziness. May cause irritation or asthma-like symptoms.
Symptoms/injuries after skin contact	: May cause slight irritation . Itching. Red skin. Skin rash/inflammation.
Symptoms/injuries after eye contact	: May cause slight eye irritation . Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Insufficient data available on direct fire hazard (flashpoint > 200°C).
-------------	---

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources.
------------------	----------------------------

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM (64742-47-8)

USA ACGIH	ACGIH TWA (ppm)	200 ppm 8 Hours
-----------	-----------------	-----------------

8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods.
Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.
Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Wear respiratory protection.
Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Color : Colourless to light yellow.
Odor : Kerosene.
Odor threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : 0.19
Melting point : -58 °C
Freezing point : No data available
Boiling point : 222 - 247 °C
Flash point : 94.7 °C
Auto-ignition temperature : 236 °C
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : 0.013 kPa
Relative vapor density at 20 °C : 4.5
Relative density : 0.804
Solubility : Insoluble in water.
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : 1.92 cSt @ 40 deg C
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM (f)64742-47-8	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h Based on lack of mortality and systemic effects

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : Dizziness. May cause irritation or asthma-like symptoms.

Symptoms/injuries after skin contact : May cause slight irritation . Itching. Red skin. Skin rash/inflammation.

Symptoms/injuries after eye contact : May cause slight eye irritation . Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM (64742-47-8)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM (64742-47-8)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not regulated,

ICAO/IATA (air): Not regulated,

IMO/IMDG (water): Not regulated,

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM (64742-47-8)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	--

15.2. International regulations

CANADA

JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM (64742-47-8)

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information


Other information : None.

Full text of H-phrases: see section 16:

Asp. Tox. 1	Aspiration hazard Category 1
H304	May be fatal if swallowed and enters airways

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.



JOHNSEN'S ENGINE FLUSH 55 GALLON DRUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,
and are not reactive with water.

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 1 Slight Hazard
Physical : 0 Minimal Hazard
Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.