



# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/07/2015

Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON  
Product code : 2415C

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Brake Parts Cleaner

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
Repr. 2 H361  
STOT SE 1 H370  
STOT SE 3 H336

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H361 - Suspected of damaging fertility or the unborn child  
H370 - Causes damage to organs

Precautionary statements (GHS-US) :

P201 - Obtain special instructions  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, ventilating, lighting equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P260 - Do not breathe dust, fumes, gas, mist, vapor, spray  
P261 - Avoid breathing dust, fume, gas, mist, vapor, spray  
P264 - Wash affected areas thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves, protective clothing, eye protection, face protection  
P302+P352 - If on skin: Wash with plenty of soap and water  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P307+P311 - If exposed: Call a poison center/doctor

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention  
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.  
P321 - Specific treatment: See section 4.1 on SDS  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS US)

6.6 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
6.6 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Acetone	(CAS No) 67-64-1	85 - 95	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Heptane, Branched Cyclic	(CAS No) 426260-76-6	6.336 - 6.6	Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Methanol	(CAS No) 67-56-1	1 - 5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370
n-Heptane	(CAS No) 142-82-5	1.65 - 2.97	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Toluene	(CAS No) 108-88-3	0.066 - 0.264	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

The exact percentage is a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Fatal if swallowed. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation : Coughing. Irritation of the respiratory tract. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness.

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after skin contact	: Itching. Red skin. Skin rash/inflammation. Causes skin irritation.
Symptoms/injuries after eye contact	: Redness of the eye tissue. Inflammation/damage of the eye tissue. Irritation of the eye tissue. Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

#### 6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.
Emergency procedures	: Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area. Do not breathe dust,fumes,gas,mist,vapor spray.
Hygiene measures	: Wash contaminated clothing before reuse. Wash affected areas thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof place. Keep container tightly closed.

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>Benzene (71-43-2)</b>		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH STEL (ppm)	5 ppm
USA ACGIH	ACGIH Ceiling (ppm)	25 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	5 ppm
<b>Toluene (108-88-3)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	75 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
<b>n-Heptane (142-82-5)</b>		
USA ACGIH	ACGIH TWA (ppm)	400 ppm (Heptane, all isomers; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (ppm)	500 ppm (Heptane, all isomers; USA; Short time value; TLV - Adopted Value)
<b>Heptane, Branched Cyclic (426260-76-6)</b>		
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm
<b>Methanol (67-56-1)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	262 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (ppm)	200 ppm (Methanol; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	328 mg/m <sup>3</sup>
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
<b>Acetone (67-64-1)</b>		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1188 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	1782 mg/m <sup>3</sup>
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.  
Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.  
Eye protection : Chemical goggles or safety glasses.

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Other information	: Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colourless to light yellow.
Odor	: Acetone odour. Solvent-like odour.
Odor threshold	: No data available
pH	: 7
Relative evaporation rate (butyl acetate=1)	: 6
Relative evaporation rate (ether=1)	: 2
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 56 °C (Lowest Component)
Flash point	: -8 °C
Critical temperature	: 235 °C (Lowest Component)
Auto-ignition temperature	: 465 °C (Lowest Component)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.78
Solubility	: Poorly soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

#### 9.2. Other information

VOC content	: 10 %
-------------	--------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Benzene (71-43-2)</b>	
LD50 oral rat	> 930 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; > 2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 8240 mg/kg (Rabbit; Experimental value; 21 CFR 191.10; > 9.4; Rabbit)
LC50 inhalation rat (mg/l)	43.767 mg/l/4h (Rat; Experimental value)
LC50 inhalation rat (ppm)	13700 ppm/4h (Rat; Experimental value)
<b>Toluene (108-88-3)</b>	
LD50 oral rat	5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)
<b>n-Heptane (142-82-5)</b>	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
<b>Heptane, Branched Cyclic (426260-76-6)</b>	
LD50 oral rat	> 15000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit; Literature study; Equivalent or similar to OECD 402; >2000 mg/kg bodyweight; Rabbit; Read-across)
LC50 inhalation rat (mg/l)	103 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	25000 ppm/4h (Rat; Literature study)
<b>Methanol (67-56-1)</b>	
LD50 oral rat	>= 2528 mg/kg body weight application as 50% aqueous solution
LD50 dermal rabbit	17100 mg/kg corresponding to 20 ml/kg bw according to the authors
LC50 inhalation rat (mg/l)	128.2 mg/l/4h Air
<b>Acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	20000 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	71 mg/l/4h (Rat; Experimental value; 76 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	30000 ppm/4h (Rat; Experimental value)

Skin corrosion/irritation	: Causes skin irritation. pH: 7
Serious eye damage/irritation	: Causes serious eye irritation. pH: 7
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

<b>Benzene (71-43-2)</b>	
IARC group	1
<b>Toluene (108-88-3)</b>	
IARC group	3

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Causes damage to organs. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Coughing. Irritation of the respiratory tract. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Itching. Red skin. Skin rash/inflammation. Causes skin irritation.
Symptoms/injuries after eye contact	: Redness of the eye tissue. Inflammation/damage of the eye tissue. Irritation of the eye tissue. Causes serious eye irritation.

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

#### 12.1. Toxicity

<b>Benzene (71-43-2)</b>	
LC50 fish 1	5.3 mg/l (LC50; 96 h; Salmo gairdneri)
EC50 Daphnia 2	10 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna)
Threshold limit algae 1	100 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

<b>n-Heptane (142-82-5)</b>	
EC50 Daphnia 1	0.2 mg/l (LC50; Other; 96 h; Chaetogammarus marinus; Semi-static system; Salt water; Experimental value)

<b>Acetone (67-64-1)</b>	
EC50 Daphnia 2	12600 mg/l (LC50; Other; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)

<b>Methanol (67-56-1)</b>	
LC50 fish 1	15400 mg/l (LC50; EPA 660/3 - 75/009; 96 h; Lepomis macrochirus; Flow-through system; Fresh water; Experimental value)
EC50 Daphnia 1	> 10000 mg/l (EC50; DIN 38412-11; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	10800 mg/l (LC50; 96 h; Salmo gairdneri)

<b>Acetone (67-64-1)</b>	
LC50 fish 1	6210 mg/l (96 h; Pimephales promelas; Nominal concentration)
EC50 Daphnia 1	8800 mg/l (48 h; Daphnia pulex)
LC50 fish 2	5540 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
TLM fish 1	13000 ppm (96 h; Gambusia affinis; Turbulent water)
TLM fish 2	> 1000 ppm (96 h; Pisces)
Threshold limit other aquatic organisms 1	3000 mg/l (Plankton)
Threshold limit other aquatic organisms 2	28 mg/l (Protozoa)
Threshold limit algae 1	7500 mg/l (Scenedesmus quadricauda; pH = 7)
Threshold limit algae 2	3400 mg/l (48 h; Chlorella sp.)

#### 12.2. Persistence and degradability

<b>JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON</b>	
Persistence and degradability	Not established.

<b>Benzene (71-43-2)</b>	
Persistence and degradability	Readily biodegradable in water. Ozonation in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	2.18 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.15 g O <sub>2</sub> /g substance
ThOD	3.10 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.70

<b>Toluene (108-88-3)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	2.15 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.52 g O <sub>2</sub> /g substance
ThOD	3.13 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.69

<b>n-Heptane (142-82-5)</b>	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	1.92 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.06 g O <sub>2</sub> /g substance
ThOD	3.52 g O <sub>2</sub> /g substance
BOD (% of ThOD)	> 0.5 (5 days; Literature study)

<b>Heptane, Branched Cyclic (426260-76-6)</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.



# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Acetone (67-64-1)</b>	
Persistence and degradability	Not established.
<b>Methanol (67-56-1)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.42 g O <sub>2</sub> /g substance
ThOD	1.5 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.8 (Literature study)
<b>Acetone (67-64-1)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available. Not established.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.20 g O <sub>2</sub> /g substance
BOD (% of ThOD)	(20 day(s)) 0.872
<b>12.3. Bioaccumulative potential</b>	
<b>JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON</b>	
Bioaccumulative potential	Not established.
<b>Benzene (71-43-2)</b>	
BCF fish 1	19 (BCF)
BCF fish 2	< 10 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 3 days; Leuciscus idus; Flow-through system; Fresh water; Experimental value)
BCF other aquatic organisms 1	30 (BCF; 24 h; Chlorella sp.)
Log Pow	2.13 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>Toluene (108-88-3)</b>	
BCF fish 2	90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>n-Heptane (142-82-5)</b>	
BCF other aquatic organisms 1	552 (BCF; BCFBAF v3.00)
Log Pow	4.66 (Experimental value; 4.5; Literature study)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).
<b>Heptane, Branched Cyclic (426260-76-6)</b>	
Bioaccumulative potential	Not established.
<b>Acetone (67-64-1)</b>	
Bioaccumulative potential	Not established.
<b>Methanol (67-56-1)</b>	
BCF fish 1	< 10 (BCF; 72 h; Leuciscus idus)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>Acetone (67-64-1)</b>	
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3
Log Pow	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative. Not established.
<b>12.4. Mobility in soil</b>	
<b>Benzene (71-43-2)</b>	
Surface tension	0.029 N/m (20 °C)
Log Koc	Koc,134.1; QSAR
<b>Toluene (108-88-3)</b>	
Surface tension	0.03 N/m (20 °C)
<b>n-Heptane (142-82-5)</b>	
Surface tension	0.019 N/m (25 °C; 0.020 N/m; 20 °C)
Log Koc	log Koc,SRC PCKOCWIN v2.0; 2.38; Calculated value



# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Methanol (67-56-1)</b>	
Surface tension	0.023 N/m (20 °C)
Log Koc	Koc,PCKOCWIN v1.66; 1; Calculated value
<b>Acetone (67-64-1)</b>	
Surface tension	0.0237 N/m (20 °C)

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN1993, Flammable liquids, n.o.s. (Acetone, Heptane, Methanol) (-8C CC), 3, II  
ICAO/IATA (air): UN1993, Flammable liquids, n.o.s. (Acetone, Heptane, Methanol) (-8C CC), 3, II  
IMO/IMDG (water): UN1993, Flammable liquids, n.o.s. (Acetone, Heptane, Methanol) (-8C CC), 3, II  
Special Provisions: IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling  
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F)  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, n.o.s. (Acetone, Heptane, Methanol) (-8C CC)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling  
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F)  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

#### Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded

#### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L  
CFR 175.75)

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
-------------------------------------	---

#### Benzene (71-43-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

#### Toluene (108-88-3)

Subject to reporting requirements of United States SARA Section 313  
Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on the United States SARA Section 302

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
-------------------------------------	---

#### Heptane, Branched Cyclic (426260-76-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	---

#### Methanol (67-56-1)

Subject to reporting requirements of United States SARA Section 313  
Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Listed on the United States SARA Section 302  
Listed on the United States SARA Section 355

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
-------------------------------------	---

#### Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard
-------------------------------------	---

### 15.2. International regulations

#### CANADA

#### JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

WHMIS Classification	Class B Division 2 - Flammable Liquid
----------------------	---------------------------------------

#### Benzene (71-43-2)

Listed on the Canadian DSL (Domestic Substances List)

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Toluene (108-88-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Heptane, Branched Cyclic (426260-76-6)</b>	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Methanol (67-56-1)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Acetone (67-64-1)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects

### EU-Regulations

<b>Toluene (108-88-3)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
<b>Heptane, Branched Cyclic (426260-76-6)</b>	
<b>Methanol (67-56-1)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
<b>Acetone (67-64-1)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F; R11  
Xn; R20/21/22  
Xn; R68/20/21/22  
Xi; R36  
N; R51/53  
R66

Full text of R-phrases: see section 16

### 15.2.2. National regulations

<b>Benzene (71-43-2)</b>	
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory	
<b>Toluene (108-88-3)</b>	
<b>Heptane, Branched Cyclic (426260-76-6)</b>	
All components are either listed on the US TSCA Inventory, or are not regulated under TSCA under 40 CFR 720.30.	
<b>Methanol (67-56-1)</b>	
Listed on the Canadian IDL (Ingredient Disclosure List)	
<b>Acetone (67-64-1)</b>	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECI (Korean Existing Chemicals Inventory) Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List)	

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON				
U.S. - California - Proposition 65 - Carcinogens List		No		
U.S. - California - Proposition 65 - Developmental Toxicity		No		
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		No		
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		No		
State or local regulations		U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)		
Benzene (71-43-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	Yes	No	Yes	
Toluene (108-88-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	
n-Heptane (142-82-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Heptane, Branched Cyclic (426260-76-6)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Acetone (67-64-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Methanol (67-56-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	
Acetone (67-64-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	
Benzene (71-43-2)				
State or local regulations				
U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL) U.S. - Pennsylvania - RTK (Right to Know) List New Jersey Right-to-Know				

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)
<b>State or local regulations</b>
U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL) U.S. - New Jersey - Special Health Hazards Substances List New Jersey Right-to-Know U.S. - Massachusetts - Right To Know List Rhode Island Right to Know U.S. - Michigan - Critical Materials List U.S. - New Jersey - Environmental Hazardous Substances List U.S. - Illinois - Toxic Air Contaminants U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Methanol (67-56-1)
<b>State or local regulations</b>
U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL) New Jersey Right-to-Know Florida Right to Know U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List
Acetone (67-64-1)
<b>State or local regulations</b>
U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL) Benzene 71-43-2 U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

Other information : None.


Full text of H-phrases:

H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

# JOHNSEN'S NON-CHLORINATED BRAKE PARTS CLEANER CALIFORNIA 5 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*