

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 09/22/2016 Supersedes: 10/20/2015 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : JOHNSEN'S SMOKE ELIMINATOR WITH STOP LEAK 14.5 FL.OZ.

Product code : 4628

Other means of identification : This product is not hazardous in accordance with US OSHA 29CFR1910.1200 (Hazcom 2012),

Canada Hazardous Products Regulations (WHMIS 2015) and the Globally Harmonized System

(GHS).

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Oil Treatment

1.3. Details of the supplier of the safety data sheet

Technical Chemical Company P.O. BOX 139 Cleburne, Texas 76033 T 817-645-6088

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labeling

No labeling applicable

2.3. Other hazards

Other hazards not contributing to the

classification

: None under normal conditions

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Heavy Hydrotreated Petroleum	(CAS No) 64742-52-5	>= 95	Not classified
Residues (Petroleum), Atmospheric	(CAS No) 68333-22-2	3 - 8	Not classified

The exact percentage is a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest. Remove victim to fresh air and keep at

rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : If you feel unwell, seek medical advice. Not expected to present a significant hazard under anticipated conditions of normal use.

22/09/2016 EN (English US) 1/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after inhalation Danger of serious damage to health by prolonged exposure through inhalation. Harmful if

inhaled.

: May cause slight irritation . Itching. Red skin. Skin rash/inflammation. Symptoms/injuries after skin contact

May cause slight eye irritation . Irritation of the eye tissue. Inflammation/damage of the eye Symptoms/injuries after eye contact

tissue. Redness of the eye tissue.

Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

Extinguishing media

: Foam. Dry powder. Carbon dioxide. Water spray. Sand. Suitable extinguishing media

Unsuitable extinguishing media : Do not use a heavy water stream.

Special hazards arising from the substance or mixture

No additional information available

Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the

leak, cut off the supply.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Use only outdoors or in a well-ventilated area. Avoid breathing

dust,fume,gas,mist,vapor spray.

Wash hands and other exposed areas with mild soap and water before eating, drinking or Hygiene measures

smoking and when leaving work. Wash affected areas thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes. Separate working

clothes from town clothes. Launder separately.

Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with

applicable regulations.

Keep only in the original container in a cool, well ventilated place away from : Keep container Storage conditions

closed when not in use.

Incompatible products Strong bases. Strong acids. Incompatible materials : Sources of ignition. Direct sunlight.

Specific end use(s)

Follow Label Directions.

22/09/2016 EN (English US) 2/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

3.1. Control parameters

orn control parameters				
JOHNSEN'S SMOKE ELIMINATOR WITH STOP LEAK 14.5 FL.OZ.				
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³ Mist 8 Hours		
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³ Mist 8 Hours		
Heavy Hydrotreated Petroleum (64742-52-5)				
USA ACGIH	ACGIH TWA (mg/m³)	5 mg/m³ MIST 8 HOURS		
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³ MIST 8 HOURS		

8.2. Exposure controls

Appropriate engineering controls : Local exhaust venilation, vent hoods . Ensure good ventilation of the work station.

Personal protective equipment : Safety glasses. Gloves. Avoid all unnecessary exposure.





Materials for protective clothing : GIVE EXCELLENT RESISTANCE:

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.

Color : Colourless to light yellow.

Odor : Petroleum-like odour. Mild . Hydrocarbon.

Odor threshold : No data available

pH : Neutral

Relative evaporation rate (butyl acetate=1) : No data available

Relative evaporation rate (ether=1) : 1000 times slower than ethyl ether

Melting point: No data availableFreezing point: No data available

Boiling point : $> 260 \, ^{\circ}\text{C}$ Flash point : $210 \, ^{\circ}\text{C}$ Auto-ignition temperature : $> 343 \, ^{\circ}\text{C}$

Decomposition temperature : No data available Flammability (solid, gas) : No data available

Vapor pressure : < 0.001 mm Hg @ 20 deg C

Relative vapor density at 20 $^{\circ}$ C : > 5 Relative density : 0.9

Solubility : Insoluble in water. Log Pow : No data available : No data available Log Kow Viscosity, kinematic : > 25 cSt @ 40 deg C Viscosity, dynamic : No data available : No data available Explosive properties Oxidizing properties : No data available **Explosion limits** : No data available

9.2. Other information

VOC content : < 1 %

22/09/2016 EN (English US) 3/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

OFOTION	40 01-1-111	All the second sections of the second
SECTION	10: Stability and	n reactivity
CECITOIN	TO. OLUBINITY WITH	a reactivity

10.1. Reactivity

No additional information available

Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

Conditions to avoid 10.4.

Direct sunlight. Extremely high or low temperatures.

Incompatible materials

Strong acids. Strong bases.

Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity : Not classified

Heavy Hydrotreated Petroleum (64742-52-5)		
LD50 oral rat	> 5000 mg/kg body weight	
LD50 dermal rabbit	> 2000 mg/kg body weight	
LC50 inhalation rat (mg/l)	5.7 mg/l/4h	

Skin corrosion/irritation : Not classified

> pH: Neutral : Not classified

pH: Neutral Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Heavy Hydrotreated Petroleum (64742-52-5) IARC group

: Not classified Reproductive toxicity Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure)

Serious eye damage/irritation

: Not classified

: Not classified Aspiration hazard

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met. Harmful if inhaled.

: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if

3

Symptoms/injuries after inhalation

inhaled.

Symptoms/injuries after skin contact

: May cause slight irritation . Itching. Red skin. Skin rash/inflammation.

Symptoms/injuries after eye contact

May cause slight eye irritation . Irritation of the eye tissue. Inflammation/damage of the eye

tissue. Redness of the eye tissue.

Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

Toxicity

No additional information available

Persistence and degradability

JOHNSEN'S SMOKE ELIMINATOR WITH STOP LEAK 14.5 FL.OZ.			
Persistence and degradability	Not established.		
Heavy Hydrotreated Petroleum (64742-52-5)			
Persistence and degradability	Not established.		

12.3 Bioaccumulative potential

JOHNSEN'S SMOKE ELIMINATOR WITH STO	P LEAK 14.5 FL.OZ.		
Bioaccumulative potential	Not established.		

22/09/2016 EN (English US) 4/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Heavy Hydrotreated Petroleum (64742-52-5
--

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to appropriate waste disposal facility, in accordance with local, regional,

national, international regulations. . Avoid release to the environment.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not regulated, ICAO/IATA (air): Not regulated, IMO/IMDG (water): Not regulated,

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

JOHNSEN'S SMOKE ELIMINATOR WITH STOP LEAK 14.5 FL.OZ.

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on on the United States EPA list of carcinogens

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

Heavy Hydrotreated Petroleum (64742-52-5)

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

15.2. International regulations

CANADA

JOHNSEN'S SMOKE ELIMINATOR WITH STOP LEAK 14.5 FL.OZ.

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Heavy Hydrotreated Petroleum (64742-52-5)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

EU-Regulations

JOHNSEN'S SMOKE ELIMINATOR WITH STOP LEAK 14.5 FL.OZ.

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

Full text of R-phrases: see section 16

22/09/2016 EN (English US) 5/6

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2.2. National regulations

No additional information available

15.3. US State regulations

JOHNSEN'S SMOKE ELIMINATOR WITH STOP LEAK 14.5 FL.OZ.		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	

Heavy Hydrotreated Petroleum (64742-52-5)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	
No	No	No	No		

Residues (Petroleum), Atmospheric (68333-22-2)					
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)	
No	No	No	No		

Heavy Hydrotreated Petroleum (64742-52-5)

State or local regulations

New Jersey Right-to-Know

SECTION 16: Other information

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual

injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard
Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

22/09/2016 EN (English US) 6/6