



# JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/03/2017

Supersedes:10/20/2015

Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.  
Product code : 4918

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Radiator Sealer

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin Sens. 1 H317

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) : Warning  
Hazard statements (GHS-US) : H317 - May cause an allergic skin reaction  
Precautionary statements (GHS-US) : P261 - Avoid breathing dust,fume,gas,mist,vapor spray  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear protective gloves,protective clothing,eye protection,face protection  
P302+P352 - If on skin: Wash with plenty of soap and water  
P321 - Specific treatment: See section 4.1 on SDS  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P363 - Wash contaminated clothing before reuse  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Water	(CAS No) 7732-18-5	>= 95	Not classified
35/60 Mesh	(CAS No) 84012-43-1	1 - 5	Not classified
Diatomaceous Earth, Uncalcined	(CAS No) 61790-53-2	1 - 5	Not classified
Acrylic Polymer	(CAS No) Confidential	< 1	Not classified
2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol	(CAS No) 4719-04-4	< 1	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
DI - Water	(CAS No) 7789-20-0	< 1	Not classified

# JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Diethanolamine	(CAS No) 111-42-2	< 1	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT RE 2, H373

The exact percentage is a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : If you feel unwell, seek medical advice.
- Symptoms/injuries after inhalation : May cause an allergic skin reaction.
- Symptoms/injuries after skin contact : May cause slight irritation . May cause moderate irritation. Itching. Skin rash/inflammation.
- Symptoms/injuries after eye contact : Irritation of the eye tissue. May cause slight eye irritation . Inflammation/damage of the eye tissue. Redness of the eye tissue.
- Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid breathing dust, fume, gas, mist, vapor spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Take off immediately all contaminated clothing and wash it before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.

#### 7.3. Specific end use(s)

Follow Label Directions.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Diethanolamine (111-42-2)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (Diethanolamine; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)

#### 8.2. Exposure controls

- Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
- Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



- Materials for protective clothing : GIVE EXCELLENT RESISTANCE:
- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Wear appropriate mask.
- Environmental exposure controls : Avoid release to the environment.
- Consumer exposure controls : Avoid contact during pregnancy/while nursing.
- Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Color : Brown.
- Odor : Mild . Earthy.
- Odor threshold : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : > 100 °C
- Flash point : > 93.9 °C (Lowest Component)
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : No data available

# JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.991
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

VOC content : < 1 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Acrylic Polymer (Confidential)</b>	
LD50 dermal rabbit	> 2000 mg/kg

<b>2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)</b>	
LD50 oral rat	763 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	0.371 mg/l/4h (Rat; Experimental value)

<b>Diethanolamine (111-42-2)</b>	
LD50 oral rat	620 mg/kg (Rat)
LD50 dermal rabbit	7640 mg/kg (Rabbit)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

<b>Diatomaceous Earth, Uncalcined (61790-53-2)</b>	
IARC group	3

<b>Diethanolamine (111-42-2)</b>	
IARC group	3

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified

# JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause an allergic skin reaction.
Symptoms/injuries after skin contact	: May cause slight irritation . May cause moderate irritation. Itching. Skin rash/inflammation.
Symptoms/injuries after eye contact	: Irritation of the eye tissue. May cause slight eye irritation . Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: May be harmful if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Acrylic Polymer (Confidential)</b>	
LC50 fish 1	10 - 100 mg/l based on component data freshwater fish.
EC50 other aquatic organisms 2	10 - 100 mg/l based on component data freshwater invertebrates.
<b>2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)</b>	
LC50 fish 1	16.07 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio; Static system; Fresh water; Experimental value)
EC50 Daphnia 1	11.9 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
EC50 Daphnia 2	8.75 mg/l (EC0; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	6.66 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value)
Threshold limit algae 2	1.56 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Experimental value)
<b>Diethanolamine (111-42-2)</b>	
LC50 fish 1	1664 mg/l (LC50; 96 h; Pimephales promelas)
EC50 Daphnia 2	55 mg/l (EC50; 48 h)

### 12.2. Persistence and degradability

<b>JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.</b>	
Persistence and degradability	Not established.
<b>DI - Water (7789-20-0)</b>	
Persistence and degradability	Not established.
<b>Acrylic Polymer (Confidential)</b>	
Persistence and degradability	Not established.
<b>35/60 Mesh (84012-43-1)</b>	
Persistence and degradability	Not established.
<b>Diatomaceous Earth, Uncalcined (61790-53-2)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
<b>2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>Water (7732-18-5)</b>	
Persistence and degradability	Not established.
<b>Diethanolamine (111-42-2)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.22 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.52 g O <sub>2</sub> /g substance
ThOD	2.13 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.1

### 12.3. Bioaccumulative potential

<b>JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.</b>	
Bioaccumulative potential	Not established.
<b>DI - Water (7789-20-0)</b>	
Bioaccumulative potential	Not established.
<b>Acrylic Polymer (Confidential)</b>	
Bioaccumulative potential	Not established.

# JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>35/60 Mesh (84012-43-1)</b>	
Bioaccumulative potential	Not established.
<b>Diatomaceous Earth, Uncalcined (61790-53-2)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)</b>	
Log Pow	-4.67 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Water (7732-18-5)</b>	
Bioaccumulative potential	Not established.
<b>Diethanolamine (111-42-2)</b>	
Log Pow	-2.18 - -1.43 (Experimental value)
Bioaccumulative potential	Bioaccumulation: not applicable.

### 12.4. Mobility in soil

<b>2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)</b>	
Log Koc	log Koc,PCKOCWIN v1.66; 1; Calculated value; Koc; PCKOCWIN v1.66; 10; Calculated value

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Avoid release to the environment.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not Regulated,

ICAO/IATA (air): Not Regulated,

IMO/IMDG (water): Not Regulated,

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not Regulated

### 14.3. Additional information

Other information : No supplementary information available.

### Overland transport

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.</b>	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
<b>Acrylic Polymer (Confidential)</b>	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

# JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

### 15.2.2. National regulations

No additional information available

### 15.3. US State regulations

JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.				
U.S. - California - Proposition 65 - Carcinogens List		No		
U.S. - California - Proposition 65 - Developmental Toxicity		No		
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		No		
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		No		
State or local regulations		U.S. - California - Proposition 65		
DI - Water (7789-20-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Acrylic Polymer (Confidential)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
35/60 Mesh (84012-43-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Diatomaceous Earth, Uncalcined (61790-53-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
2,2',2''-(Hexahydro-1,3,5-Triazine-1,3,5-Triyl) Triethanol (4719-04-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Water (7732-18-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Diethanolamine (111-42-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

# JOHNSEN'S RADIATOR STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Acrylic Polymer (Confidential)</b>
<b>State or local regulations</b>
U.S. - California - Proposition 65
<b>Diethanolamine (111-42-2)</b>
<b>State or local regulations</b>
U.S. - California - Proposition 65


### SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.  
NFPA fire hazard : 1 - Must be preheated before ignition can occur.  
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible  
Flammability : 1 Slight Hazard  
Physical : 0 Minimal Hazard  
Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*