



# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 08/18/2016

Supersedes:02/16/2016

Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON  
Product code : 5055

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Brake Fluid

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Acute Tox. 4 (Oral) H302  
Acute Tox. 4 (Inhalation:dust,mist) H332  
Skin Irrit. 2 H315  
Eye Dam. 1 H318  
Repr. 2 H361

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS05

GHS07

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H302+H332 - Harmful if swallowed or if inhaled  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H361 - Suspected of damaging fertility or the unborn child

Precautionary statements (GHS-US) : P201 - Obtain special instructions  
P202 - Do not handle until all safety precautions have been read and understood  
P261 - Avoid breathing dust,fume,gas,mist,vapor spray  
P264 - Wash affected areas thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves,protective clothing,eye protection,face protection  
P301+P312 - If swallowed: Call a poison center, doctor if you feel unwell  
P302+P352 - If on skin: Wash with plenty of soap and water  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P310 - Immediately call a poison center,doctor, physician  
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.  
P321 - Specific treatment: See section 4.1 on SDS  
P330 - Rinse mouth  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P405 - Store locked up  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Triethylene Glycol Monomethyl Borate Ester	(CAS No) 30989-05-0	15 - 40	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Irrit. 2B, H320
Triethylene Glycol Monomethyl Ether	(CAS No) 112-35-6	10 - 30	Not classified
Methoxy Polyethylene Glycol 350	(CAS No) 9004-74-4	10 - 30	Not classified
Triethylene Glycol Monobutyl Ether	(CAS No) 143-22-6	8 - 18	Eye Dam. 1, H318
Polyalkylene Glycol Monobutyl Ether	(CAS No) 9004-77-7	7 - 13	Not classified
Tetraethylene Glycol	(CAS No) 112-60-7	<= 10	Not classified
3,6,9,12-Tetraoxatetradecane-1,14-diol	(CAS No) 4792-15-8	1 - 5	Not classified
Triethyleneglycol	(CAS No) 112-27-6	1 - 5	Not classified
Diisopropanolamine	(CAS No) 110-97-4	<= 1.5	Not classified
Sodium Hydroxide	(CAS No) 1310-73-2	< 1	Skin Corr. 1A, H314
2,6-Di-tert-butyl-p-cresol	(CAS No) 128-37-0	< 1	Acute Tox. 4 (Oral), H302
Diethylene Glycol Monomethyl Ether	(CAS No) 111-77-3	< 1	Flam. Liq. 4, H227 Repr. 2, H361

The exact percentage is a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes damage to organs. Suspected of damaging fertility or the unborn child.

Symptoms/injuries after inhalation : Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.

Symptoms/injuries after skin contact : May cause moderate irritation. Itching. Red skin. Skin rash/inflammation. Causes skin irritation.

Symptoms/injuries after eye contact : Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye damage.

Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

##### 6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill. Plug the leak, cut off the supply. Contain released substance, pump into suitable containers.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Use only outdoors or in a well-ventilated area. Avoid breathing dust, fume, gas, mist, vapor spray. Obtain special instructions. Do not handle until all safety precautions have been read and understood.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage area : Keep only in the original container.

Special rules on packaging : Keep only in original container.

#### 7.3. Specific end use(s)

Follow Label Directions.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Sodium Hydroxide (1310-73-2)		
USA ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (Sodium hydroxide; USA; Momentary value; TLV - Adopted Value)
2,6-Di-tert-butyl-p-cresol (128-37-0)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup> (Butylated hydroxytoluene (BHT); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)

#### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods. Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.

# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colourless to light yellow.
Odor	: Mild . Ammoniacal.
Odor threshold	: No data available
pH	: 7.7
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: < -59 °C
Freezing point	: No data available
Boiling point	: 281 °C
Flash point	: 132 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: < 0.01 mm Hg Estimated
Relative vapor density at 20 °C	: > 10
Relative density	: 1.03 - 1.08
Solubility	: Soluble in water. Water: 100% Estimated
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 1100 mm <sup>2</sup> /s @ -40 deg C Estimated
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

#### 9.2. Other information

VOC content	: 0 %
-------------	-------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Not established.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

#### 10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	: Oral: Harmful if swallowed. Inhalation:dust,mist: Harmful if inhaled.
----------------	---

#### Triethylene Glycol Monomethyl Ether (112-35-6)

LD50 oral rat	11865 mg/kg (Rat)
---------------	-------------------

# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Triethylene Glycol Monomethyl Ether (112-35-6)</b>	
LD50 dermal rabbit	7455 mg/kg (Rabbit)
<b>Methoxy Polyethylene Glycol 350 (9004-74-4)</b>	
LD50 oral rat	22000 mg/kg (Rat)
LD50 dermal rabbit	> 20000 mg/kg (Rabbit)
<b>Triethylene Glycol Monobutyl Ether (143-22-6)</b>	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	3480 mg/kg (Rabbit)
<b>Tetraethylene Glycol (112-60-7)</b>	
LD50 oral rat	29000 mg/kg (Rat)
LD50 dermal rabbit	> 20000 mg/kg (Rabbit)
<b>Triethyleneglycol (112-27-6)</b>	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit)
<b>Diisopropanolamine (110-97-4)</b>	
LD50 oral rat	4765 mg/kg (Rat)
LD50 dermal rat	16000 mg/kg (Rat)
LD50 dermal rabbit	8000 mg/kg (Rabbit)
<b>Triethylene Glycol Monomethyl Borate Ester (30989-05-0)</b>	
LD50 oral rat	> 5 g/kg
LD50 dermal rabbit	> 2 g/kg
LC50 inhalation rat (mg/l)	200 mg/l
<b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>	
LD50 oral rat	890 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value; >6000 mg/kg bodyweight; Rat)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; OECD 402: Acute Dermal Toxicity; >2000 mg/kg bodyweight; Rat; Experimental value)
<b>Diethylene Glycol Monomethyl Ether (111-77-3)</b>	
LD50 oral rat	4140 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	> 20 mg/l/4h (Rat)
Skin corrosion/irritation	: Causes skin irritation. pH: 7.7
Serious eye damage/irritation	: Causes serious eye damage. pH: 7.7
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
<b>Polyalkylene Glycol Monobutyl Ether (9004-77-7)</b>	
IARC group	4
<b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>	
IARC group	3
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed. Harmful if inhaled.
Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. Harmful if inhaled.
Symptoms/injuries after skin contact	: May cause moderate irritation. Itching. Red skin. Skin rash/inflammation. Causes skin irritation.
Symptoms/injuries after eye contact	: Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue. Causes serious eye damage.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 12: Ecological information

#### 12.1. Toxicity

<b>Triethylene Glycol Monomethyl Ether (112-35-6)</b>	
LC50 fish 1	> 5000 mg/l (LC50; 96 h)
EC50 Daphnia 1	> 10000 mg/l (LC50; 48 h)
Threshold limit algae 1	> 500 mg/l (EC50; 72 h)
<b>Triethylene Glycol Monobutyl Ether (143-22-6)</b>	
LC50 fish 2	2200 mg/l (LC50; 96 h)
EC50 Daphnia 2	> 500 mg/l (EC50; 48 h)
Threshold limit algae 1	> 500 mg/l (EC50; 72 h)
<b>Triethyleneglycol (112-27-6)</b>	
EC50 Daphnia 1	42426 mg/l (EC50; 48 h)
LC50 fish 2	61000 mg/l (LC50; 96 h; <i>Lepomis macrochirus</i> )
Threshold limit algae 2	> 10000 mg/l (EC0; 168 h)
<b>Diisopropanolamine (110-97-4)</b>	
LC50 fish 1	1000 - 2200 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; <i>Brachydanio rerio</i> )
EC50 Daphnia 2	277.7 mg/l (EC50; 48 h)
Threshold limit algae 1	270 mg/l (EC50; 72 h)
<b>Sodium Hydroxide (1310-73-2)</b>	
LC50 fish 1	45.4 mg/l (LC50; Other; 96 h; <i>Salmo gairdneri</i> ; Static system; Fresh water; Experimental value)
<b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>	
LC50 fish 1	>= 0.57 mg/l (LC0; EU Method C.1; 96 h; <i>Brachydanio rerio</i> ; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 1	0.48 mg/l (EC50; OECD 202: <i>Daphnia</i> sp. Acute Immobilisation Test; 48 h; <i>Daphnia magna</i> ; Static system; Fresh water; Experimental value)
LC50 fish 2	0.199 mg/l (LC50; ECOSAR v1.00; 96 h; Pisces)
EC50 Daphnia 2	0.15 mg/l (NOEC; OECD 202: <i>Daphnia</i> sp. Acute Immobilisation Test; 48 h; <i>Daphnia magna</i> ; Static system; Fresh water; Experimental value)
<b>Diethylene Glycol Monomethyl Ether (111-77-3)</b>	
LC50 fish 1	1000 mg/l (LC50; 96 h)
EC50 Daphnia 1	> 500 mg/l (EC50; 48 h)
Threshold limit algae 1	> 500 mg/l (EC50; 72 h)
<b>12.2. Persistence and degradability</b>	
<b>JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON</b>	
Persistence and degradability	Not established.
<b>Triethylene Glycol Monomethyl Ether (112-35-6)</b>	
Persistence and degradability	Inherently biodegradable. Non degradable in the soil. Photodegradation in the air. Not established.
<b>Methoxy Polyethylene Glycol 350 (9004-74-4)</b>	
Persistence and degradability	Not readily biodegradable in water.
BOD (% of ThOD)	0.1 (28 days)
<b>Triethylene Glycol Monobutyl Ether (143-22-6)</b>	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.02 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.83 g O <sub>2</sub> /g substance
<b>Tetraethylene Glycol (112-60-7)</b>	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.50 g O <sub>2</sub> /g substance (10d)
ThOD	2.23 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.286
<b>Polyalkylene Glycol Monobutyl Ether (9004-77-7)</b>	
Persistence and degradability	Not established.
<b>3,6,9,12-Tetraoxatetradecane-1,14-diol (4792-15-8)</b>	
Persistence and degradability	Biodegradability in water: no data available.
<b>Triethyleneglycol (112-27-6)</b>	
Persistence and degradability	Inherently biodegradable. Readily biodegradable in water. Photolysis in the air.

# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Triethyleneglycol (112-27-6)</b>	
Biochemical oxygen demand (BOD)	0.03 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.57 g O <sub>2</sub> /g substance
ThOD	1.6 g O <sub>2</sub> /g substance
<b>Diisopropanolamine (110-97-4)</b>	
Persistence and degradability	Not readily biodegradable in water.
<b>Triethylene Glycol Monomethyl Borate Ester (30989-05-0)</b>	
Persistence and degradability	Not established.
<b>Sodium Hydroxide (1310-73-2)</b>	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
<b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>	
Persistence and degradability	Not readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photooxidation in the air.
Biochemical oxygen demand (BOD)	0.51 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.27 g O <sub>2</sub> /g substance
ThOD	2.977 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.17
<b>Diethylene Glycol Monomethyl Ether (111-77-3)</b>	
Persistence and degradability	Readily biodegradable in water. Photolysis in the air. Photodegradation in the air.
Chemical oxygen demand (COD)	1.71 g O <sub>2</sub> /g substance
ThOD	1.73 g O <sub>2</sub> /g substance
<b>12.3. Bioaccumulative potential</b>	
<b>JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON</b>	
Bioaccumulative potential	Not established.
<b>Triethylene Glycol Monomethyl Ether (112-35-6)</b>	
Log Pow	-1.13
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.
<b>Methoxy Polyethylene Glycol 350 (9004-74-4)</b>	
Bioaccumulative potential	Not bioaccumulative.
<b>Triethylene Glycol Monobutyl Ether (143-22-6)</b>	
Log Pow	0.51 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Tetraethylene Glycol (112-60-7)</b>	
Log Pow	-2.18 - -1.38
Bioaccumulative potential	Bioaccumulation: not applicable.
<b>Polyalkylene Glycol Monobutyl Ether (9004-77-7)</b>	
Bioaccumulative potential	Not established.
<b>3,6,9,12-Tetraoxatetradecane-1,14-diol (4792-15-8)</b>	
Log Pow	-2.30 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.
<b>Triethyleneglycol (112-27-6)</b>	
Log Pow	-2.08 - -1.17 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
<b>Diisopropanolamine (110-97-4)</b>	
Log Pow	-0.79
Bioaccumulative potential	Bioaccumulation: not applicable.
<b>Triethylene Glycol Monomethyl Borate Ester (30989-05-0)</b>	
Bioaccumulative potential	Not established.
<b>Sodium Hydroxide (1310-73-2)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>	
BCF fish 1	230 - 2500 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 56 days; Cyprinus carpio; Flow-through system; Fresh water; Experimental value)

# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2,6-Di-tert-butyl-p-cresol (128-37-0)	
Log Pow	5.1 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation ( $500 \leq BCF \leq 5000$ ).

Diethylene Glycol Monomethyl Ether (111-77-3)	
Log Pow	-1.14 - -0.68
Bioaccumulative potential	Bioaccumulation: not applicable.

### 12.4. Mobility in soil

Triethylene Glycol Monomethyl Ether (112-35-6)	
Surface tension	0.0314 N/m

Methoxy Polyethylene Glycol 350 (9004-74-4)	
Surface tension	0.04 N/m

Tetraethylene Glycol (112-60-7)	
Surface tension	0.019 N/m

Triethyleneglycol (112-27-6)	
Surface tension	0.045 N/m (20 °C)

2,6-Di-tert-butyl-p-cresol (128-37-0)	
Log Koc	Koc,PCKOCWIN v1.66; 23030; Calculated value; log Koc; PCKOCWIN v1.66; 4.362; Calculated value
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

Diethylene Glycol Monomethyl Ether (111-77-3)	
Surface tension	0.035 N/m (25 °C)

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not regulated,

ICAO/IATA (air): Not regulated,

IMO/IMDG (water): Not regulated,

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated

### 14.3. Additional information

Other information : No supplementary information available.

### Overland transport

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard



# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Triethylene Glycol Monomethyl Ether (112-35-6)

Subject to reporting requirements of United States SARA Section 313

### Triethylene Glycol Monobutyl Ether (143-22-6)

Subject to reporting requirements of United States SARA Section 313

### Triethylene Glycol Monomethyl Borate Ester (30989-05-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. International regulations

### CANADA

#### JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

Listed on the Canadian DSL (Domestic Substances List)

#### Triethylene Glycol Monobutyl Ether (143-22-6)

#### Triethylene Glycol Monomethyl Borate Ester (30989-05-0)

Listed on the Canadian DSL (Domestic Substances List)

## EU-Regulations

#### Triethylene Glycol Monobutyl Ether (143-22-6)

#### Triethylene Glycol Monomethyl Borate Ester (30989-05-0)

Listed on ELINCS (European List of Notified Chemical Substances)

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

## Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xi; R41

Xi; R38

R52/53

Full text of R-phrases: see section 16

## 15.2.2. National regulations

#### JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

#### Triethylene Glycol Monobutyl Ether (143-22-6)

#### Triethylene Glycol Monomethyl Borate Ester (30989-05-0)

## 15.3. US State regulations

### JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

U.S. - California - Proposition 65 - Carcinogens List

Yes

U.S. - California - Proposition 65 - Developmental Toxicity

Yes

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

Yes

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

Yes

State or local regulations

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)  
U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - New Jersey - Right to Know Hazardous Substance List

### Triethylene Glycol Monomethyl Ether (112-35-6)

U.S. - California - Proposition 65 - Carcinogens List

U.S. - California - Proposition 65 - Developmental Toxicity

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

Non-significant risk level (NSRL)

No

No

No

No

### Methoxy Polyethylene Glycol 350 (9004-74-4)

U.S. - California - Proposition 65 - Carcinogens List

U.S. - California - Proposition 65 - Developmental Toxicity

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

Non-significant risk level (NSRL)

No

No

No

No

# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Triethylene Glycol Monobutyl Ether (143-22-6)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Tetraethylene Glycol (112-60-7)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Polyalkylene Glycol Monobutyl Ether (9004-77-7)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>3,6,9,12-Tetraoxatetradecane-1,14-diol (4792-15-8)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Triethyleneglycol (112-27-6)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Diisopropanolamine (110-97-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Triethylene Glycol Monomethyl Borate Ester (30989-05-0)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Sodium Hydroxide (1310-73-2)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
<b>Diethylene Glycol Monomethyl Ether (111-77-3)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

# JOHNSEN'S DOT 4 BRAKE FLUID DRUM 55 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Triethylene Glycol Monomethyl Ether (112-35-6)</b>
<b>State or local regulations</b>
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - New Jersey - Right to Know Hazardous Substance List
<b>Triethylene Glycol Monobutyl Ether (143-22-6)</b>
<b>State or local regulations</b>
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - New Jersey - Right to Know Hazardous Substance List
<b>Triethyleneglycol (112-27-6)</b>
<b>State or local regulations</b>
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
<b>Triethylene Glycol Monomethyl Borate Ester (30989-05-0)</b>
<b>State or local regulations</b>
U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

### SECTION 16: Other information

Indication of changes : Revision - See : \*

Other information : None.


Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H320	Causes eye irritation
H332	Harmful if inhaled
H361	Suspected of damaging fertility or the unborn child

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*