



# JOHNSEN'S R404A 24 POUND CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 09/15/2016

Supersedes:12/03/2014

Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : JOHNSEN'S R404A 24 POUND CYLINDER  
Product code : 6404

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Refrigerant Gas

#### 1.3. Details of the supplier of the safety data sheet

Technical Chemical Company  
P.O. BOX 139  
Cleburne, Texas 76033  
T 817-645-6088

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Liquefied gas H280

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS04

Signal word (GHS-US) : Warning  
Hazard statements (GHS-US) : H280 - Contains gas under pressure; may explode if heated  
Precautionary statements (GHS-US) : P410+P403 - Protect from sunlight. Store in a well-ventilated place  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated. Intentional misuse and inhalation abuse may cause cardiac or central nervous systems effects. Warning. May Cause frostbite in contact with skin. May Cause frostbite in contact with skin. (Liquid form can be ejected if the aerosol can is not held upright during use.) Warning. This product dispenses liquid. Liquid may drip onto skin causing frostbite, blistering, red skin. WARNING. . Asphyxiant in high concentrations. . None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
1,1,1-Trifluoroethane, Liquid, Under Pressure 76143	(CAS No) 420-46-2	50 - 70	Liquefied gas, H280
Pentafluoroethane	(CAS No) 354-33-6	30 - 50	Liquefied gas, H280
1,1,1,2-Tetrafluoroethane	(CAS No) 811-97-2	1 - 5	Liquefied gas, H280

The exact percentage is a trade secret.

# JOHNSEN'S R404A 24 POUND CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.
First-aid measures after inhalation	: Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Rinse with water. Take victim to a doctor if irritation persists. In case of frostbites: Wash immediately with lots of water (15 minutes)/shower. Do not apply (chemical) neutralizing agents. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to an ophthalmologist.
First-aid measures after ingestion	: Not applicable.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Feeling of weakness. Central nervous system depression. Headache. Nausea. Dizziness. Mental confusion. Coordination disorders. Accelerated heart action. Disturbances of heart rate. Disturbances of consciousness. Respiratory difficulties.
Symptoms/injuries after skin contact	: Dry skin. Frostbites.
Symptoms/injuries after eye contact	: Frostbites.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: NFPA Aerosol Level 1.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources.
------------------	----------------------------

##### 6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. Provide equipment/receptacles with earthing.
Methods for cleaning up	: Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use.
-----------------------------------	---

# JOHNSEN'S R404A 24 POUND CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash affected areas thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### 8.2. Exposure controls

Appropriate engineering controls	: Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure. Gloves. Safety glasses.



Materials for protective clothing	: GIVE EXCELLENT RESISTANCE:
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Consumer exposure controls	: Avoid contact during pregnancy/while nursing.
Other information	: Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Liquefied gas.
Molecular mass	: 97.6 g/mol
Colour	: Colourless.
Odour	: Faint Ethereal Odor.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: -47.8 °C
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 8445 mm Hg @ 21.1 deg C
Relative vapour density at 20 °C	: No data available
Relative density	: 1.05
Solubility	: Moderately soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available

# JOHNSEN'S R404A 24 POUND CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: 100 % VOC Exempted
-------------	----------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified as hazardous

#### 1,1,1-Trifluoroethane, Liquid, Under Pressure 76143 (420-46-2)

LC50 inhalation rat (mg/l)	> 1848 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	> 540000 ppm/4h (Rat)

#### Pentafluoroethane (354-33-6)

LC50 inhalation rat (mg/l)	2910 mg/l/4h (Rat)
----------------------------	--------------------

#### 1,1,1,2-Tetrafluoroethane (811-97-2)

LC50 inhalation rat (mg/l)	> 2000 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	> 359300 ppm/4h (Rat; Literature study)

Skin corrosion/irritation	: Not classified as hazardous
Serious eye damage/irritation	: Not classified as hazardous
Respiratory or skin sensitisation	: Not classified as hazardous
Germ cell mutagenicity	: Not classified as hazardous
Carcinogenicity	: Not classified as hazardous
Reproductive toxicity	: Not classified as hazardous
Specific target organ toxicity (single exposure)	: Not classified as hazardous
Specific target organ toxicity (repeated exposure)	: Not classified as hazardous
Aspiration hazard	: Not classified as hazardous
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Feeling of weakness. Central nervous system depression. Headache. Nausea. Dizziness. Mental confusion. Coordination disorders. Accelerated heart action. Disturbances of heart rate. Disturbances of consciousness. Respiratory difficulties.
Symptoms/injuries after skin contact	: Dry skin. Frostbites.
Symptoms/injuries after eye contact	: Frostbites.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### 1,1,1-Trifluoroethane, Liquid, Under Pressure 76143 (420-46-2)

LC50 fish 1	> 40 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Flow-through system; Fresh water; Experimental value)
-------------	--

# JOHNSEN'S R404A 24 POUND CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>1,1,1-Trifluoroethane, Liquid, Under Pressure 76143 (420-46-2)</b>	
EC50 Daphnia 1	300 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Literature)
Threshold limit algae 1	71 mg/l (EC50; ECOSAR; 72 h; Algae)

<b>1,1,1,2-Tetrafluoroethane (811-97-2)</b>	
LC50 fish 1	450 mg/l (LC50; 96 h)
EC50 Daphnia 1	980 mg/l (EC50; 48 h)

### 12.2. Persistence and degradability

<b>JOHNSEN'S R404A 24 POUND CYLINDER</b>	
Persistence and degradability	Not established.

<b>1,1,1-Trifluoroethane, Liquid, Under Pressure 76143 (420-46-2)</b>	
Persistence and degradability	Not readily biodegradable in water.

<b>Pentafluoroethane (354-33-6)</b>	
Persistence and degradability	Not readily biodegradable in water.

<b>1,1,1,2-Tetrafluoroethane (811-97-2)</b>	
Persistence and degradability	Not readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>JOHNSEN'S R404A 24 POUND CYLINDER</b>	
Bioaccumulative potential	Not established.

<b>1,1,1-Trifluoroethane, Liquid, Under Pressure 76143 (420-46-2)</b>	
Log Pow	1.74 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>Pentafluoroethane (354-33-6)</b>	
Log Pow	1.48
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>1,1,1,2-Tetrafluoroethane (811-97-2)</b>	
BCF other aquatic organisms 1	5 - 58 (BCF)
Log Pow	1.06 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Refer to manufacturer/supplier for information on recovery/recycling.

Additional information : LWCA (the Netherlands): KGA category 06. Hazardous waste according to Directive 2008/98/EC.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): UN3337, Refrigerant gas R404A (1,1,1-Trifluoroethane, Pentafluoroethane, 1,1,1,2-Tetrafluoroethane), 2.2  
ICAO/IATA (air): UN3337, Refrigerant gas R404A (1,1,1-Trifluoroethane, Pentafluoroethane, 1,1,1,2-Tetrafluoroethane), 2.2  
IMO/IMDG (water): UN3337, Refrigerant gas R404A (1,1,1-Trifluoroethane, Pentafluoroethane, 1,1,1,2-Tetrafluoroethane), 2.2  
Special Provisions: T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Refrigerant gas R404A (1,1,1-Trifluoroethane, Pentafluoroethane, 1,1,1,2-Tetrafluoroethane)  
Class (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

# JOHNSEN'S R404A 24 POUND CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Special Provisions (49 CFR 172.102) : T50 - When portable tank instruction T50 is referenced in Column (7) of the 172.101 Table, the applicable liquefied compressed gases are authorized to be transported in portable tanks in accordance with the requirements of 173.313 of this subchapter

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 304

DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

#### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel

#### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg  
CFR 175.75)

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### JOHNSEN'S R404A 24 POUND CYLINDER

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard
-------------------------------------	--

#### 1,1,1,2-Tetrafluoroethane (811-97-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard
-------------------------------------	--

### 15.2. International regulations

#### CANADA

#### JOHNSEN'S R404A 24 POUND CYLINDER

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class A - Compressed Gas
----------------------	--------------------------

#### 1,1,1,2-Tetrafluoroethane (811-97-2)

WHMIS Classification	Class A - Compressed Gas
----------------------	--------------------------

#### EU-Regulations

No additional information available

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

F+; R12

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

No additional information available

### 15.3. US State regulations

#### JOHNSEN'S R404A 24 POUND CYLINDER

U.S. - California - Proposition 65 - Carcinogens List	No
---	----

# JOHNSEN'S R404A 24 POUND CYLINDER

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

JOHNSEN'S R404A 24 POUND CYLINDER	
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

1,1,1-Trifluoroethane, Liquid, Under Pressure 76143 (420-46-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Pentafluoroethane (354-33-6)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

1,1,1,2-Tetrafluoroethane (811-97-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

### SECTION 16: Other information

Other information : None.


Full text of H-statements:

H280	Contains gas under pressure; may explode if heated
------	--

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



### HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard

Physical : 1 Slight Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.